



Art. no. **5903**

## Art. no. 5903

Mobile parts cleaner in painted steel, with closed circuit of detergent fluid, consisting of storage container with 65 l capacity with two wheels and two castors, cleaning basin with closable and removable cover, fluid-permeable cleaning brush which permits a continuous flow of the detergent and an accurate cleaning of parts, blow gun with rigid outlet. The system enables a continuous fluid circulation by pressurizing the container with compressed air at max. 0.5 bar.

Note: please use only suitable detergents and degreasing agents for the parts cleaning.



Art. no. **7705**

Detergent for parts cleaners, in 20 l – plastic can.

Art. no.	Compressed air supply	Max pressure	Capacity cleaning basin	Capacity container	Weight	Dimensions (LxWxH) (mm)
<b>5903</b>	0.5 bar	0.5 bar	60 l	65 l	42 kg	560x700x1000



Art. no. **5908**

## Art. no. 5908

Mobile parts cleaner in painted steel, with closed circuit of detergent fluid, consisting of cleaning basin with closable and removable cover, fluid-permeable cleaning brush which permits a continuous flow of the detergent and an accurate cleaning of parts, blow gun with rigid outlet and shelf for the placing of plastic cans or drums, with 4 castors.

The system enables a continuous fluid circulation by the use of a pneumatic rotary pump in stainless steel (art. no. 1058).

Note: please use only suitable detergents and degreasing agents for the parts cleaning.

Art. no.	Compressed air supply	Max pressure	Capacity cleaning basin	Weight	Dimensions (LxWxH) (mm)
<b>5908</b>	1-4 bar	4 bar	60 l	36 kg	560x700x810



Art. no. **5953**

## Art. no. 5953

Mobile parts cleaner, with closed circuit of detergent fluid, consisting of cleaning basin in stainless steel AISI 304 with closable and removable cover, fluid-permeable cleaning brush which permits a continuous flow of the detergent and an accurate cleaning of parts, blow gun with rigid outlet and shelf for the placing of plastic cans or drums, with 4 castors. The system enables a continuous fluid circulation by the use of a pneumatic rotary pump in stainless steel (art. no. 1058).

Note: please use only suitable detergents and degreasing agents for the parts cleaning.

Art. no.	Compressed air supply	Max pressure	Capacity cleaning basin	Weight	Dimensions (LxWxH) (mm)
<b>5953</b>	4 bar	4 bar	60 l	36 kg	560x700x810

