


Art.no. **3185**  
Art.no. **3185/110**

Mobile low level gravity waste oil drainer, suitable for the draining of motor oil, gear oil or differential oil from trucks and passenger cars. Available with collection capacity of 70 l and 110 l, with anti splash grid and removable, lateral antisplash guard (optional). The unit can be discharged by gravity through the laterally mounted 3/4" drain valve or by using an evacuation pump with suction hose and female quick coupling to be connected to the male coupling installed on the drainer (see evacuation kit art. no. 2044 + 2264 on page 115!).



Art. no.	Collection capacity	Connections	Weight	Dimensions (LxWxH) (mm)
<b>3185</b>	70 l	3/4" BSP (F)	26 Kg	800x560x180
<b>3185/110</b>	110 l	3/4" BSP (F)	38 Kg	1400x560x180




Art.no. **3185/20**

Mobile low level gravity waste oil drainer such as above, but in height-reduced version, ideal for the use with passenger cars with sports chassis.



Art. no.	Collection capacity	Connections	Weight	Dimensions (LxWxH) (mm)
<b>3185/20</b>	22 l	3/4" BSP (F)	18 Kg	800x500x80



Art.no. **3254**  
Art.no. **3254/110**

Mobile low level gravity drainer, suitable for the draining of waste oils and antifreeze from trucks and passenger cars by using the included pump kit for the eventual refilling of the liquid into the motor or circuit after finishing the service.

Available with collection capacity of 70 l and 110 l, with anti splash grid.

The pump kit art.no. 3246 consists of a pneumatic rotary pump (art.no. 1058, see page 52), pressure regulator with manometer, suction hose and dispensing hose with control dispensing nozzle and rigid outlet pipe.

On demand also pump kit art.no. 3248 with pneumatic diaphragm pump (art.no. 8319, see page 115) instead of pneumatic rotary pump is available.



Art. no.	Compressed air supply	Outlet pressure	Delivery	Collection capacity	Connections	Weight	Dimensions (LxWxH) (mm)
<b>3254</b>	2-4 bar	4 bar	10 l/min	70 l	1/2" BSP (F)	34 Kg	800x560x180
<b>3254/110</b>	2-4 bar	4 bar	10 l/min	110 l	1/2" BSP (F)	46 Kg	800x560x285

