FLEXBIMEC

AUTOMATIC REWIND, SPRING - DRIVEN HOSE REELS

Heavy duty series Ø max 3/4" - up to 30 m length Ø max 1" - up to 25 m length

Automatic rewind, spring-driven hose reel, **heavy duty series,** in painted steel or in stainless steel AISI 304, suitable for hoses of max 30 m length (ø hose 3/4") or max. 25 m length (ø hose 1").

The art.no. 9036 is equipped with a twin spring for a convenient hose rewind.

The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, diesel, compressed air and water at low pressure. Please see catalogue pages 220 and 221 for the selection of the required hoses.

On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix "/HB" to the article number (f. ex. 9034/HB)!











On demand the stainles steel hose reels can also be supplied in

cordance with directive

ATEX 2014/34/EUgroup II – category 2.

Art.no. **9768** Art.no. **9764** Art.no. **9765**

Art.no.	Material	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 3/4" - 1"	Suitable pivoting wall bracket	Included swivel joint	Dimensions (A-B-C) (mm)	Spool width (D)	Weight
9030	Painted steel Stainless steel AISI 304	- 100 bar	1" (M) - 1" (F)	20 mm	1"	12 m - 8 m	9768	9969	295x530x500	150 mm	21 Kg
9034						18 m - 15 m	9769		440x530x500	300 mm	24 Kg
9036						30 m - 25 m	-		500x530x540	400 mm	36 Kg
9529						12 m - 8 m	9765	9986	295x530x500	150 mm	21 Kg
9525						18 m - 15 m	9764		440x530x500	300 mm	24 Kg
9536						30 m - 25 m	-		500x530x540	400 mm	36 Kg



OPTIONAL

/HB Hydraulic spring brake kit (patented)

Safety device for the controlled rewind of hoses, installable on all spring-driven hose reel models, eliminating the dangers caused by an uncontrolled rewind or a sudden release of the hose when unwinded during its use.







