



## Art.no. 4290/X

Electronic oval gears grease flow meter, series **NEPTUNE X**, with grease control gun, rigid outlet pipe and hydraulic 4 – jaws – coupler. The calibration of the meter can also be made by the user. Equipped with 3 AA batteries.

## Art.no. 4290/RF

Electronic oval gears flow meter for grease, series **GREASE JUPITER 4TT** 4-button line, with grease control gun and a radio frequency data transmission to be used in combination with the **RF CONNECT** control unit. The calibration of the meter can also be made by the user.

## Art.no. 4291/X

Electronic oval gears grease flow meter, series **NEPTUNE X**, suitable for the use as inline meter. The calibration of the meter can also be made by the user.

## Art.no. 4291/RF

Electronic oval gears flow meter for grease, series **GREASE JUPITER 4TT** 4-button line, with a radio frequency data transmission to be used in combination with the **RF CONNECT** control unit. The calibration of the meter can also be made by the user.

| Art.no.                    | 4290/X - 4290/RF   | 4291/X - 4291/RF |
|----------------------------|--------------------|------------------|
| Connections                | 1/4" BSP (M)       | 1/4" BSP (F)     |
| Flow rate min – max        | 0.20 - 2 kg/min    |                  |
| Temperature                | + 5°C / + 50°C     |                  |
| Max pressure               | 400 bar (5801 psi) |                  |
| Precision                  | ± 0.3% *           |                  |
| Total max (resettable)     | 999.9 kg           |                  |
| Total max (non-resettable) | 9999 kg            |                  |
| Voltage                    | 3 x 1.5 V          |                  |
| Weight                     | 1.4 kg             | 1.2 kg           |

\*Basic calibration made in factory with grease NLGI 0

# 4TT

## PRESET FUNCTION



The preset function introduces a certain degree of automation since it becomes possible to predetermine the dosages and automatically stop the grease flow once the preselected value has been reached.

The calibration of the meter can also be made by the user.

## Art.no. 4292

Electronic oval gears **grease** flow meter, series **"Grease Mercury"**, with **preset function** of the desired grease quantity to be supplied. With grease control gun, rigid outlet pipe and hydraulic 4 – jaws – coupler.

## Art.no. 4292/RF

Electronic oval gears flow meter for **grease**, series **GREASE URANUS**, with preset function, with the same characteristics of art. no. 4292 but with radio frequency data transmission to be used in combination with the **RF CONNECT** control unit.

| Art.no.                    | 4292 - 4292/RF     |
|----------------------------|--------------------|
| Connections                | 1/4" BSP (M)       |
| Flow rate min – max        | 0.20 - 2 kg/min    |
| Temperature                | + 5°C / + 50°C     |
| Max pressure               | 300 bar (4351 psi) |
| Precision                  | ± 1%*              |
| Lowest preselection value  | 0.010 kg           |
| Total max (resettable)     | 999.9 kg           |
| Total max (non-resettable) | 9999 kg            |
| Voltage                    | 3 x 1.5 V          |
| Weight                     | 1.7 kg             |

\*Basic calibration made in factory with grease NLGI 0