

Art.no. 8730

Electronic oval gears flow meter with pulse transmitter, suitable for oil, diesel and antifreeze, including a 24 VDC - solenoid valve, an in-line 125 µm cartridge filter and a wall bracket.



Art.no. 8733 Electronic oval gears flow meter with pulse transmitter, such as art. no. 8730, for grease.

Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Number of pulses	Weight	Dimensions (LxWxH) (mm)
8730	1/2" BSP (F)	20 l/min	+5°C / +80°C	100 bar (1450 psi)	+ / - 0,5%	95/l	1.5 kg	120X120X160
8733				250 bar (3626 psi)				

Art.no. 8731

Electronic oval gears flow meter with pulse transmitter, suitable for oil, diesel and antifreeze, including a 24 VDC - solenoid valve, an in-line 105 µm cartridge filter and a wall bracket. Appropriate to the use in combination with electronic oil monitoring systems by the use of an external receiver.



Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Number of pulses	Weight	Dimensions (LxWxH) (mm)
8731	F 1" BSP	35 l/min	+5°C / +80°C	30 bar (435 psi)	+ / - 1%	50/l	2.5 kg	120X120X175

Art.no. 8732

Electronic oval gears flow meter with pulse transmitter, suitable for oil, diesel and antifreeze, including an in-line 125 µm cartridge filter, **a built-in display** and a wall bracket.



Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Number of pulses	Weight	Dimensions (LxWxH) (mm)
8732	1/2" BSP (F)	20 l/min	+5°C / +80°C	100 bar (1450 psi)	+ / - 0.5%	100/l	1.5 kg	120X120X160

Art.no. 8735

Electronic oval gears flow meter with pulse transmitter, body in Arnite, including a stainless steel 24 VDC - solenoid valve, an in-line 125 µm cartridge filter and a wall bracket. Suitable for the use with water-based fluids and AdBlue® (DEF). Appropriate to the use in combination with electronic oil monitoring systems by the use of an external receiver.



Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Number of pulses	Weight	Dimensions (LxWxH) (mm)
8735	1/2" BSP (F)	10 l/min	+5°C / +80°C	10 bar (145 psi)	+ / - 0.5%	95/l	1.5 kg	120X120X160