



Non-return valve with poppet.  
Body in galvanized steel.  
Opening pressure 0.5 bar (on demand also 4 bar or 8 bar).  
Connections (BSP): F – F.



| Art. no.    | Connections | Max pressure | Max flow rate |
|-------------|-------------|--------------|---------------|
| <b>6639</b> | 1/4" BSP    | 400 bar      | 30 l/min      |
| <b>6641</b> | 1/2" BSP    | 350 bar      | 90 l/min      |
| <b>6643</b> | 3/4" BSP    | 300 bar      | 130 l/min     |
| <b>6640</b> | 1" BSP      | 280 bar      | 180 l/min     |
| <b>6648</b> | 1 1/4" BSP  | 260 bar      | 250 l/min     |


Unidirectional flow regulator valve.  
Body in galvanized steel.  
Connections (BSP): F – F.



| Art. no.    | Connections | Regulation range A - B | Max pressure | Max flow rate A - B | Max flow rate B - A |
|-------------|-------------|------------------------|--------------|---------------------|---------------------|
| <b>6650</b> | 1/2" BSP    | from 0 to 50 l/min     | 350 bar      | 50 l/min            | 80 l/min            |
| <b>6651</b> | 3/4" BSP    | from 0 to 80 l/min     | 300 bar      | 80 l/min            | 110 l/min           |
| <b>6652</b> | 1" BSP      | from 0 to 110 l/min    | 250 bar      | 110 l/min           | 140 l/min           |

Hose burst valve to automatically block increases in flow rate resulting from line failures or breaks.

Body in galvanized steel.  
Connections (BSP): F – M.



| Art. no.    | Connections | Max pressure | Max flow rate |
|-------------|-------------|--------------|---------------|
| <b>6670</b> | 1/2" BSP    | 350 bar      | 80 l/min      |
| <b>6671</b> | 3/4" BSP    | 350 bar      | 150 l/min     |
| <b>6672</b> | 1" BSP      | 350 bar      | 180 l/min     |

4-way flow diverter in cast iron, open center, with limited pressure drops.  
With 2 fixation holes Ø 8,5 mm.



Art.nos.  
**6675 - 6676**



Art.no. **6677**



| Art. no.    | Connections | Max pressure | Max flow rate |
|-------------|-------------|--------------|---------------|
| <b>6675</b> | 1/2" BSP    | 250 bar      | 50 l/min      |
| <b>6676</b> | 3/4" BSP    | 220 bar      | 90 l/min      |
| <b>6677</b> | 1" BSP      | 160 bar      | 150 l/min     |