



Non-return valve with poppet.
Body in galvanized steel.
Opening pressure 0.5 bar (on demand also 4 bar or 8 bar).
Connections (BSP): F – F.



Art. no.	Connections	Max pressure	Max flow rate
6639	1/4" BSP	400 bar	30 l/min
6641	1/2" BSP	350 bar	90 l/min
6643	3/4" BSP	300 bar	130 l/min
6640	1" BSP	280 bar	180 l/min
6648	1 1/4" BSP	260 bar	250 l/min


Unidirectional flow regulator valve.
Body in galvanized steel.
Connections (BSP): F – F.



Art. no.	Connections	Regulation range A - B	Max pressure	Max flow rate A - B	Max flow rate B - A
6650	1/2" BSP	from 0 to 50 l/min	350 bar	50 l/min	80 l/min
6651	3/4" BSP	from 0 to 80 l/min	300 bar	80 l/min	110 l/min
6652	1" BSP	from 0 to 110 l/min	250 bar	110 l/min	140 l/min

Hose burst valve to automatically block increases in flow rate resulting from line failures or breaks.

Body in galvanized steel.
Connections (BSP): F – M.



For correct operation, the valve must be calibrated to a flow rate 1.5-2 times higher than the maximum working flow rate.

Art. no.	Connections	Max pressure	Max flow rate
6670	1/2" BSP	350 bar	80 l/min
6671	3/4" BSP	350 bar	150 l/min
6672	1" BSP	350 bar	180 l/min

4-way flow diverter in cast iron, open center, with limited pressure drops.
With 2 fixation holes Ø 8,5 mm.



Art. no.	Connections	Max pressure	Max flow rate
6675	1/2" BSP	250 bar	50 l/min
6676	3/4" BSP	220 bar	90 l/min
6677	1" BSP	160 bar	150 l/min