

55 l/min

Art.no. **6738**

Diesel transfer kit, with electric 230 VAC – pump, mounted on wall bracket.

Composed of selfpriming electric pump with built-in bypass valve and inlet strainer, ON-/OFF switch, 2 m – cable with plug and fuse, mechanical flow meter (art. no. 2866), 4 m - rubber delivery hose Ø 3/4", 2 m – suction hose Ø 25 mm, suction foot valve with filter (art. no. 6647) and automatic shut-off dispensing nozzle with inlet swivel (art. no. 6725).



Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6738	230 VAC 50Hz	370 W	1.5 A	2800	55 l/min	1" BSP (F)	18 Kg	400x400x290



99 l/min

Art.no. **6739**

Diesel transfer kit, with electric 230 VAC – pump, mounted on wall bracket.

Composed of selfpriming electric pump with built-in bypass valve and inlet strainer, ON-/OFF switch, 2 m – cable with plug and fuse, mechanical flow meter (art. no. 2865), 4 m - rubber delivery hose Ø 1", 2 m – suction hose Ø 25 mm, suction foot valve with filter (art. no. 6638) and automatic shut-off dispensing nozzle with inlet swivel (art. no. 6726).



Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6739	230 VAC 50Hz	750 W	6.2 A	1400	99 l/min	1" BSP (F)	22 Kg	400x400x290



Art.no. **6755**

Diesel transfer kit, with electric 230 VAC – pump, mounted on wall bracket (art. no. 6739), but equipped with automatic rewind, spring – driven hose reel, adjustable arms series, in painted steel (art. no. 9095) with 8 m - rubber delivery hose Ø 1", 2 m – connection hose to pump and diesel/water separating cartridge filter (art. no. 6600).



Art. no.	Voltage	Power	Current drain	Rpm	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6755	230 VAC 50Hz	750 W	6.2 A	1400	60 l/min	1" BSP (F)	42 Kg	400x400x290

