

Art.no. **8735**



Electronic oval gears flow meter with pulse transmitter, body in IXEF, including a stainless steel 24 VDC - solenoid valve, an in-line 125 µm cartridge filter and a wall bracket. Suitable for the use with water-based fluids and AdBlue® (DEF).

Appropriate to the use in combination with electronic oil monitoring systems by the use of an external receiver.

Art. no.	Max working pressure	Max flow rate	Accuracy	Connection thread	Number of pulses	Weight	Dimensions (LxWxH) (mm)
8735	10 bar	10 l/min	+ / - 0.5%	1/2" BSP (F)	95/l	1.5 kg	120x120x160




Art.no. **7324**

Refractometer for checking the quality of AdBlue®.

The device is indicating the urea concentration in the fluid in percentage by weight on a scale with a light/dark separating line.

Adjustable ocular permits adaptation to the user's eyesight.

A dropper to take a sample quantity of the fluid is included.



Art.no. **2253**

Plastic suction tube, ø 27 mm, length 1100 mm, with bung adapter 2" BSP for fixation on drums or tanks and 90° - elbow adapter ø 25 mm for hose connection. Suitable for 1000 l - IBC - tanks.



Art.no. **2253**



Art.no. **2897**

Art.no. **2897**

EPDM delivery hose, ø 3/4" (sold by the meter).

Art.no. **2256**

Suction kit for AdBlue® drums and tanks, composed of plastic suction tube (in HDPE) with plug head BCS 56x4 and foot valve and SEC/CDS - suction coupling with 90° - elbow hose tile ø 20 mm for hose connections.

