

Pneumatic oil dispensing kits for 1 or 2 oil types. The use of the included spill containment pallet with metal mounting rack allows to create quickly an autonomous dispensing unit that can be put in any place of the workshop. Also it can be moved at any time if it becomes necessary.

Kit 8621

Pneumatic oil dispensing and storage cabinet, one drum - version, for 208 l - drums, consisting of:

- Tank Service Base for 1 drum of 208 l, art. no. 8525;
- Metal, lockable cabinet for 1 drum of 208 l, art. no. 8681;
- Pneumatic double acting 5:1 - oil pump, art. no. 2076 (see page 68!);
- Plastic bung adapter for the fixation of pumps on drums, art. no. 4340;
- Open hose reel, standard series, art. no. 9016;
- 15 m - rubber hose Ø 1/2", art. no. 28715;
- 2 m - rubber connection hose Ø 1/2", art. no. 28702;
- Electronic flow meter for oil, with control gun, rubber protection guard, trigger guard, flexible outlet, Ø 1/2", with curved rigid 90° stem, automatic anti-drip nozzle and inlet swivel 1/2" BSP (M), art. no. 2962 (see page 88!);
- Pressure regulator with condensate separator, lubricator and pressure gauge, art. no. 7150.

OPTIONAL

- On request, instead of the art. no. 2962, the electronic flow meter with control gun can be supplied with internal memory for the traceability of the dispensing, available in two versions with or without Radio Frequency (see pages 89/90).
- Hydraulic spring brake device for the controlled and safe rewinding of hoses. Please add suffix "/HB" to the individual hose reel article number!

Art. no.	Weight	Dimensions (LxWxH) (mm)
8621	230 Kg	830x880x2360



Kit 8634

Pneumatic oil dispensing and storage cabinet, 2 drums - version, for 208 l - drums, consisting of:

- Tank Service Base for 2 drums of 208 l, art. no. 8533;
- Metal, lockable cabinet for 2 drums of 208 l, art. no. 8682;
- 2 pcs. of pneumatic double acting 5:1 - oil pumps, art. no. 2076 (see page 68!);
- 2 pcs. of plastic bung adapters for the fixation of pumps on drums, art. no. 4340;
- 2 pcs. of open hose reels, standard series, art. no. 9016;
- 2 pcs. of 15 m - rubber hoses 1/2", art. no. 28715;
- 2 pcs. of 2 m - rubber connection hoses 1/2", art. no. 28702;
- 2 pcs. of electronic flow meters for oil, with control gun, rubber protection guard, trigger guard, flexible outlet, Ø 1/2", with curved rigid 90° stem, automatic anti-drip nozzle and inlet swivel 1/2" BSP (M), art. no. 2962 (see page 88!);
- 2 pcs. of Pressure regulator with condensate separator, lubricator and pressure gauge, art. no. 7150.

OPTIONAL

- On request, instead of the art. no. 2962, the electronic flow meter with control gun can be supplied with internal memory for the traceability of the dispensing, available in two versions with or without Radio Frequency (see pages 89/90).
- Hydraulic spring brake device for the controlled and safe rewinding of hoses. Please add suffix "/HB" to the individual hose reel article number!

Art. no.	Weight	Dimensions (LxWxH) (mm)
8634	290 Kg	1350x880x2360

