




Containers in galvanized sheet steel, wall thickness 6/10, provided for the use as a lubricants storage container with the following characteristics:

- two-wing front or lateral doors, 2300 mm (width) x 2200 mm (height), with safety lock and key, or sliding door at the long side;
- floor plate with grate, bores 76 x 34 mm;
- collecting drip pan, height 130 mm, wall thickness 20/10;
- loading rack;
- ventilation grilles (86x45cm) with fixed fins.

On demand: with integrated lighting.



Art. no.	Description	Dimensions (LxWxH) (mm)
8591	Container in galvanized sheet steel with two-wing front doors	3000 x 2000 x 2400
8592		4000 x 2000 x 2400
8593		5000 x 2300 x 2400
8594		7000 x 2300 x 2400
8591/S	Container in galvanized sheet steel with two-wing sliding doors at the long side	3000 x 2000 x 2400
8592/S		4000 x 2000 x 2400
8593/S		5000 x 2300 x 2400
8594/S		7000 x 2300 x 2400



Internal dimensions: - 100 mm in length and width, - 400 mm in height.


Heat insulated containers with panels of 30 mm wall thickness, provided for the use as a lubricants storage container with the following characteristics:

- two-wing front or lateral doors with safety lock and key, or sliding door at the long side;
- floor plate with grate, bores 76 x 34 mm;
- collecting drip pan, height 130 mm, wall thickness 20/10;
- loading rack;
- ventilation grilles with fixed fins.

On demand: lighting and power supply kit, with neon roof light, 36 W, bivalent power socket 10 – 16 A + T, residual current protective device 8 M with 3 differentials (overall – lighting – power socket).



Art. no.	Description	Dimensions (LxWxH) (mm)
8595	Heat insulated container in galvanized sheet steel with two-wing front doors	3000 x 2400 x 2400
8596		4000 x 2400 x 2400
8597		5000 x 2400 x 2400
8598		7000 x 2400 x 2400
8599		8000 x 2400 x 2400
8595/S	Heat insulated container in galvanized sheet steel with two-wing sliding doors at the long side	3000 x 2300 x 2400
8596/S		4000 x 2300 x 2400
8597/S		5000 x 2300 x 2400
8598/S		7000 x 2300 x 2400
8599/S		8000 x 2300 x 2400



Internal dimensions: - 130 mm in length and width, - 400 mm in height.

