

Electric, centrifugal transfer pumps for diesel and fuel oil, suitable for the direct mounting on drums or tanks. These non-selfpriming pumps, protection category IP 44, include motors with thermal circuit breaker, integrated siphon protection device, ON-/OFF switch and an integrated connection thread M 64 x 4 and BSP 2". On the shaft a small manual pump is mounted which serves for the filling of the suction hose as well as for a manual pumping if there is no electric power supply available.



Diesel transfer kit, composed of electric 12 VDC, 24 VDC or 230 VAC pump, 3 m – cable with alligator clamps for battery connection (12 VDC and 24 VDC) or 2 m – cable with earth contact type plug (230 VAC), 1.6 m – suction hose with foot filter, 4 m – rubber delivery hose Ø 3/4" with anti-kink spring, hose tails and **manual plastic nozzle**.

Optional: Electronic turbine flow meter (art. no. 2823).

Art. no.	Voltage	Power	Current drain	Delivery	Connection threads	Weight
6766	12 VDC	150 W	12.5 A	31 l/min	3/4" BSP	3.2 kg
6768	24 VDC	180 W	7.5 A	34 l/min		3.2 Kg
6769	230 VAC	250 W	1.2 A	38 l/min		3.6 kg



Diesel transfer kit, composed of electric 12 VDC, 24 VDC or 230 VAC pump, 3 m – cable with alligator clamps for battery connection (12 VDC and 24 VDC) or 2 m – cable with earth contact type plug, 1.6 m – suction hose with foot filter, 4 m – rubber delivery hose Ø 3/4" with anti-kink spring, hose tails and **automatic shut-off dispensing nozzle** with inlet swivel.

Optional: electronic turbine flow meter (art. no. 2823).

Art. no.	Voltage	Power	Current drain	Delivery	Connection threads	Weight
6770	12 VDC	150 W	12.5 A	31 l/min	3/4" BSP	4.1 kg
6771	24 VDC	180 W	7.5 A	34 l/min		4.1 Kg
6773	230 VAC	250 W	1.2 A	38 l/min		4.5 kg



Electric, hybrid transfer pumps for diesel, fuel oil, bio-diesel (with suitable hoses), antifreeze (with or without water), suitable for the direct mounting on drums or tanks. These pumps are selfpriming, protection category IP 54, with ON-/OFF switch and an integrated connection thread BSP 2".

Art.no. **6782**

Diesel transfer kit, composed of electric 230 VAC pump, 4 m – cable with earth contact type plug, 1.6 m – suction hose with foot filter, 4 m – rubber delivery hose Ø 3/4", high delivery automatic shut-off dispensing nozzle with inlet swivel, with electronic in-line turbine flow meter (art. no. 2823).

Art.no. **6783**

Diesel transfer kit, same as art. no. 6782, but without electronic in-line turbine flow meter.

Art. no.	Voltage	Power	Current drain	Delivery	Connection threads	Weight
6782	230 VAC	950 W	4.5 A	80 l/min	1" BSP	4.5 kg
6783	230 VAC	950 W	4.5 A	85 l/min		4.1 Kg