



Art.no. **9527/EX+289408**

Automatic rewind, spring-driven hose reel, adjustable arms series, in stainless steel AISI 304, in accordance with directive ATEX 2014/34/EU – group II – category 2, with 8 m - rubber hose Ø 1" (ø int. 25 mm), suitable for the supply of petrol in accordance with norm EN 1761:1999.




Art. no.	Max pressure	Connection threads inlet - outlet	Internal diameter inlet swivel joint	Diameter / Length delivery hose	Width reel	Weight	Dimensions (LxWxH) (mm)
9527/EX+289408	18 bar	1" BSP (M) 1" BSP (F)	20 mm	1" – 8 m	150 mm	22 kg	290x460x450

Optional



Art.no. **9765**
Swivel bracket



Art.no. **9525/EX+289415**

Automatic rewind, spring-driven hose reel, heavy duty series, in stainless steel AISI 304, in accordance with directive ATEX 2014/34/EU – group II – category 2, with 15 m - rubber hose Ø 1" (ø int. 25 mm), suitable for the supply of petrol in accordance with norm EN 1761:1999.




Art. no.	Max pressure	Connection threads inlet - outlet	Internal diameter inlet swivel joint	Diameter / Length delivery hose	Width reel	Weight	Dimensions (LxWxH) (mm)
9525/EX+289415	18 bar	1" BSP (M) 1" BSP (F)	20 mm	1" – 15 m	300 mm	38 kg	440x530x500

Optional



Art.no. **9764**
Swivel bracket



Art.no. **9536/EX+289425**

Automatic rewind, spring-driven hose reel, adjustable arms series, in stainless steel AISI 304, in accordance with directive ATEX 2014/34/EU – group II – category 2, with 25 m - rubber hose Ø 1" (ø int. 25 mm), suitable for the supply of petrol in accordance with norm EN 1761:1999.



Art. no.	Max pressure	Connection threads inlet - outlet	Internal diameter inlet swivel joint	Diameter / Length delivery hose	Width reel	Weight	Dimensions (LxWxH) (mm)
9536/EX+289425	18 bar	1" BSP (M) 1" BSP (F)	20 mm	1" – 25 m	400 mm	61 kg	500x530x540

