


AdBlue® (Diesel Exhaust Fluid (DEF)) is a solution of synthetically produced urea in de-mineralized water which is used to reduce the emissions of nitrogen oxides from the exhaust systems of diesel vehicles. The average consumption of AdBlue® is approx. 5 % of the diesel consumption. It is injected into the exhaust system of heavy diesel vehicles constructed according to norm EURO VI. These vehicles are equipped with a dedicated AdBlue® tank which requires special equipment for the refilling.

Art.no. **5496**

Lever action pump in stainless steel, gaskets in EPDM, suitable for the use in drums or in 1000 l – IBC – tanks, with 4 m – delivery hose, rigid dispensing outlet and bung adapter for fixation on drum or tank. Delivery 8 l/min.



Art.no. **03 5496**
Bung adapter 2"/60x2 for
AdBlue® drums and tanks.



Art. no.	Delivery/stroke	Delivery	Diameter bung adapter	Connection thread	Weight
5496	0.13 l	8 l/min	60 x 2	3/4" BSP (M)	2 Kg

Art.no. **5493**

Lever action polypropylene pump, suitable for the use in drums, with 2 m – PVC delivery hose, rigid dispensing outlet and bung adapter for fixation on drum or tank.



Art. no.	Delivery/stroke	Delivery	Diameter bung adapter	Connection thread	Weight
5493	0.5 l	12 l/min	60 x 2	2" BSP (M)	1.6 kg