




Art.no. **9090X + 289810**
 Art.no. **9091X + 289815**
 Art.no. **9092X + 289820**
 Art.no. **9093X + 289825**
 Art.no. **9095X + 289910**
 Art.no. **9096X + 289915**

Automatic rewind, spring-driven hose reel, in painted steel, with wetted parts (swivel joint and internal fluid shaft) in stainless steel AISI 304, with EPDM – delivery hose and connections in stainless steel.

Optional accessories:

- hydraulic spring brake device for the controlled and safe rewinding of hoses. Please add suffix **"/HB"** to the individual hose reel article number! See also information at the bottom of this page!
- Art. no. 9767B – art.no. 9768B - Swivel bracket

On demand the swivel joint and the internal shaft are also available in stainless steel AISI 316.



Art.no. **9767B**
 Art.no. **9768B**



Art.no. **9590 + 289810**
 Art.no. **9591 + 289815**
 Art.no. **9592 + 289820**
 Art.no. **9593 + 289825**
 Art.no. **9595 + 289910**
 Art.no. **9596 + 289915**

Automatic rewind, spring-driven hose reel, in stainless steel AISI 304, with wetted parts (swivel joint and internal fluid shaft) in stainless steel AISI 304, with EPDM – delivery hose and connections in stainless steel.

Optional accessories:

- hydraulic spring brake device for the controlled and safe rewinding of hoses. Please add suffix **"/HB"** to the individual hose reel article number! See also information at the bottom of this page!
- Art. no. 9760 – art.no. 9765 - Swivel bracket .

On demand the swivel joint and the internal shaft are also available in stainless steel AISI 316.



Art.no. **9760**
 Art.no. **9765**



Art. no.	Max working pressure	Connection threads IN - OUT	Diameter hose	Length hose	Spool width (F)	Suitable pivoting wall bracket	Weight	Dimensions (A-B-C) (mm)
9090X + 289810	20 bar	1/2" BSP (M) – 1/2" BSP (F)	1/2"	10 m	120 mm	9767B	15 kg	240x560x450
9091X + 289815				15 m	120 mm	9768B	16 kg	
9092X + 289820				20 m	150 mm		21 kg	270x560x450
9093X + 289825				25 m	200 mm		26 kg	305x560x450
9095X + 289910		3/4" BSP (M) – 3/4" BSP (F)	3/4"	10 m	150 mm		17 kg	270x500x490
9096X + 289915				15 m	200 mm		31 kg	305x490x490
9590 + 289810		1/2" BSP (M) – 1/2" BSP (F)	1/2"	10 m	120 mm	9760	15 kg	240x560x450
9591 + 289815				15 m	120 mm	9765	16 kg	
9592 + 289820				20 m	150 mm		21 kg	270x560x450
9593 + 289825				25 m	200 mm		26 kg	305x560x450
9595 + 289910		3/4" BSP (M) – 3/4" BSP (F)	3/4"	10 m	150 mm		24 kg	270x500x490
9596 + 289915				15 m	200 mm		31 kg	305x490x490

OPTIONAL

HB Spring brake hydraulic kit / PATENTED

Safety device for a controlled rewinding of the hose.

Restrains the hose in case of accidental releases, lowering risks for the operator.

Patent no. 0001426967

