

Electric pumps for the supply of fluids with particular chemical characteristics. It is recommended to check the compatibility of the fluid with the materials of the wetted pump components before use.

Art.no 6123

Electric, selfpriming gear pump for the transfer of various fluids and chemical products; guarantees a constant flow and a low noise level.

Pump body in IXEF, gears in plastic.

Protection category IP 55.

Includes ON/OFF – switch and 1.5 m – cable with plug.



Art. no.	Voltage	Current drain	Rpm	Power	Outlet pressure	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6123	230 VAC 50 Hz	2.4 A	1350	250 W	4 bar	15 l/min	1/2" BSP (M)	7 kg	240x290x180



Art.no 6132

Electric, selfpriming gear pump for the transfer of various fluids and chemical products; guarantees a constant flow and a low noise level.

Pump body in stainless steel AISI 304, gears in plastic.

Protection category IP 55.

Includes ON/OFF – switch and 1.5 m – cable with plug and a bypass valve preset on 5 bar pressure.



Art. no.	Voltage	Current drain	Rpm	Power	Outlet pressure	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6132	230 VAC 50 Hz	3,8 A	2760	370 W	5 bar	10.5 l/min	1/2" BSP (M)	7.5 Kg	150x300x190



Art.no 6446

Electric, centrifugal pump for the transfer of clean water.

Pump body and rotor in stainless steel AISI 304.



Art. no.	Voltage	Current drain	Power	Outlet pressure	Delivery	Connection threads	Weight	Dimensions (LxWxH) (mm)
6446	230 VAC 50 Hz	5 A	750 W	4 bar	160 l/min	1 1/4" BSP (F)	11 kg	296x206x186

