

Automatic rewind, spring-driven hose reel, **enclosed series**, in painted steel or in stainless steel AISI 304, suitable for hoses of max 20 m length (Ø hose 1/2") or max 25 m length (Ø hose 3/8"). The wetted parts of the painted steel models on demand can also be replaced by stainless steel parts (see pages 263-265). The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water. Please see catalogue pages 220 and 221 for the selection of the required hoses.

On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9013/HB)! **Please note: the spring brake kit is available only for art.nos. 9013-9547.**



Art.no. 9778



Art.no. 9754

| Art.no. | Material                 | Max working pressure | Connection threads IN - OUT | Internal diameter swivel joint | Max diameter hose | Max length hose | Suitable pivoting wall bracket | Included swivel joint | Dimensions (A-B-C) (mm) | Spool width (F) | Weight |
|---------|--------------------------|----------------------|-----------------------------|--------------------------------|-------------------|-----------------|--------------------------------|-----------------------|-------------------------|-----------------|--------|
| 9013    | Painted steel            | 600 bar              | 1/2" (M) - 1/2" (F)         | 10 mm                          | 1/2"              | 15 m            | 9778                           | 9951                  | 215x530x470             | 120 mm          | 26 Kg  |
| 9023    |                          | 600 bar              | 1/2" (M) - 1/2" (F)         | 10 mm                          | 1/2"              | 20 m            |                                |                       | 215x530x470             | 120 mm          | 27 Kg  |
| 9024    |                          | 100 bar              | 1" (M) - 3/4" (F)           | 20 mm                          | 3/4"              | 8 m             |                                | 9986                  | 245x530x470             | 150 mm          | 26 Kg  |
| 9025    |                          | 600 bar              | 1/2" (M) - 1/2" (F)         | 10 mm                          | 3/8"              | 25 m            |                                | 9951                  | 215x530x470             | 120 mm          | 29 Kg  |
| 9546    | Stainless steel AISI 304 | 100 bar              | 1" (M) - 3/4" (F)           | 20 mm                          | 3/4"              | 8 m             | 9754                           | 9986                  | 245x530x470             | 150 mm          | 26 Kg  |
| 9547    |                          | 200 bar              | 1/2" (M) - 1/2" (F)         | 10 mm                          | 1/2"              | 15 m            |                                | 9963                  | 215x530x470             | 120 mm          | 26 Kg  |
| 9548    |                          | 200 bar              | 1/2" (M) - 1/2" (F)         | 10 mm                          | 1/2"              | 20 m            |                                |                       | 245x530x470             | 150 mm          | 27 Kg  |
| 9549    |                          | 200 bar              | 1/2" (M) - 1/2" (F)         | 10 mm                          | 3/8"              | 25 m            |                                |                       | 245x530x470             | 150 mm          | 29 Kg  |

## OPTIONAL

**HB Spring brake hydraulic kit / PATENTED**  
Safety device for a controlled rewinding of the hose.

Restraints the hose in case of accidental releases, lowering risks for the operator.

**Patent no. 0001426967**

