

Automatic rewind, spring-driven hose reel, **adjustable arms series**, in painted steel or in stainless steel AISI 304, suitable for hoses of max 25 m length and max diameter of 1/2". The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water.

The wetted parts of the painted steel models on demand can also be replaced by stainless steel parts (see pages 263-265).

Please see catalogue pages 220 and 221 for the selection of the required hoses.


On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9090/HB)!



Art.no. **9767**
Art.no. **9768**



Art.no. **9760**
Art.no. **9765**



Art.no.	Material	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 3/8" - 1/2"	Suitable pivoting wall bracket	Included swivel joint	Dimensions (A-B-C) (mm)	Spool width (F)	Weight
9090	Painted steel	600 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	15 m	9767	9951	240x560x450	120 mm	12 kg
9091						20 m -15 m					15 kg
9092						25 m -20 m	9768		270x560x450	150 mm	16 kg
9093						25 m			303x560x450	200 mm	19 kg
9590	Stainless steel AISI 304	200 bar				15 m	9760	9963	240x560x450	120 mm	12 kg
9591						20 m -15 m					15 kg
9592						25 m -20 m	9765		270x560x450	150 mm	16 kg
9593						25 m			303x560x450	200 mm	19 kg



OPTIONAL

HB Spring brake hydraulic kit / PATENTED

Safety device for a controlled rewinding of the hose.

Restrains the hose in case of accidental releases, lowering risks for the operator.

Patent no. 0001426967

