

Automatic rewind, spring-driven hose reel, **adjustable arms series**, in painted steel or in stainless steel AISI 304, suitable for hoses of max 40 m length (Ø hose max. 1/2").

The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water.

The wetted parts of the painted steel models on demand can also be replaced by stainless steel parts (see pages 263-265).

Please see catalogue pages 220 and 221 for the selection of the required hoses.

On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9074/HB)!



Art.no. 9777



Art.no. 9770



On demand the stainless steel hose reels can also be supplied in accordance with directive ATEX 2014/34/EU – group II – category 2.

Art.no.	Material	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose	Suitable pivoting wall bracket	Included swivel joint	Dimensions (A-B-C) (mm)	Spool width (F)	Weight
9074	Painted steel	600 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	30 m	9777	9951	370x590x600	150 mm	25 kg
9083						35 m					26 kg
9073						40 m					30 kg
9574	Stainless steel AISI 304	200 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	30 m	9770	9963	370x590x600	150 mm	25 kg
9530						35 m					26 kg
9573						40 m					30 kg

OPTIONAL

HB Spring brake hydraulic kit / PATENTED
Safety device for a controlled rewinding of the hose.

Restraints the hose in case of accidental releases, lowering risks for the operator.

Patent no. 0001426967

