

Automatic rewind, spring-driven hose reel, **adjustable arms series**, in painted steel or in stainless steel AISI 304, suitable for hoses of max 18 m length ($\varnothing$ hose 3/4") or max. 15 m length ($\varnothing$ hose 1").

The wetted parts of the painted steel models on demand can also be replaced by stainless steel parts (see pages 263-265).

The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, diesel, compressed air and water.

Please see catalogue pages 220 and 221 for the selection of the required hoses.

On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9095/HB)!



Art.no. **9768**
Art.no. **9769**



Art.no. **9764**
Art.no. **9765**



On demand the stainless steel hose reels can also be supplied in accordance with directive ATEX 2014/34/EU – group II – category 2.

Art.no.	Material	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 3/4" - 1"	Suitable pivoting wall bracket	Included swivel joint	Dimensions (A-B-C) (mm)	Spool width (F)	Weight
9095	Painted steel	100 bar	1" (M) - 1" (F)	20 mm	1"	10 m – 8 m	9768	9986	270x500x490	150 mm	14 kg
9096						15 m -12 m			305x490x490	200 mm	22 kg
9097						18 m -15 m	9769		505x530x500	300 mm	24 kg
9595	Stainless steel AISI 304					10 m - 8 m	9765		270x500x490	150 mm	14 kg
9596						15 m -12 m			305x490x490	200 mm	22 kg
9584						18 m -15 m	9764		505x530x500	300 mm	24 kg



OPTIONAL

HB Spring brake hydraulic kit / PATENTED

Safety device for a controlled rewinding of the hose.

Restrains the hose in case of accidental releases, lowering risks for the operator.

Patent no. 0001426967

