

Automatic rewind, spring-driven hose reel, **adjustable arms series with twin spring**, in painted steel or in stainless steel AISI 304, suitable for hoses of max 30 m length ($\varnothing$ hose 3/4") or max. 20 m length ($\varnothing$ hose 1").

The wetted parts of the painted steel models on demand can also be replaced by stainless steel parts (see pages 263-265).

The hose reel is supplied without hoses and can be used with hoses for the supply of oils, diesel, compressed air and water.

Please see catalogue pages 220 and 221 for the selection of the required hoses. On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9070/HB)!



Art.no. **9777**
Art.no. **9769**



Art.no. **9770**
Art.no. **9764**



On demand the stainless steel hose reels can also be supplied in accordance with directive ATEX 2014/34/EU – group II – category 2.

Art.no.	Material	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 3/4" - 1"	Suitable pivoting wall bracket	Included swivel joint	Dimensions (A-B-C) (mm)	Spool width (F)	Weight
9084	Painted steel	100 bar	1" (M) - 1" (F)	20 mm	1"	20 m - 15 m	9777	9986	270x600x590	150 mm	27 kg
9098						25 m - 18 m			370x640x600	200 mm	30 kg
9070						30 m - 20 m	9769		450x540x600	300 mm	38 kg
9534	Stainless steel AISI 304					20 m - 15 m	9770		270x600x590	150 mm	27 kg
9598						25 m - 18 m			370x640x600	200 mm	30 kg
9570						30 m - 20 m	9764		450x540x600	300 mm	38 kg

OPTIONAL

HB Spring brake hydraulic kit / PATENTED
Safety device for a controlled rewinding of the hose.

Restrains the hose in case of accidental releases, lowering risks for the operator.

Patent no. 0001426967

