

Automatic rewind, spring-driven hose reel, **adjustable arms series with twin spring**, in painted steel or in stainless steel AISI 304, suitable for applications with high delivery rates and for hoses of max 50 m length (Ø hose 3/4") or max. 30 m length (Ø hose 1"). The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water. Please see catalogue pages 220 and 221 for the selection of the required hoses. On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9085/HB)!




 On demand the stainless steel hose reels can also be supplied in accordance with directive ATEX 2014/34/EU – group II – category 2.

Art.no.	Material	Max working pressure	Connection threads IN - OUT	Internal ø swivel joint	Max diameter hose	Max length hose	Included swivel joint	Dimensions (A-B-C) (mm)	Spool width (F)	Weight			
9085	Painted steel	100 bar	1" (M) - 1" (F)	20 mm	3/4"	40 m	9986	650x650x590	400 mm	50 kg			
9068					3/4"	50 m				52 kg			
9099					1"	30 m				50 kg			
9585	Stainless steel AISI 304				3/4"	40 m				50 kg			
9588					3/4"	50 m				52 kg			
9599					1"	30 m				50 kg			



OPTIONAL

HB Spring brake hydraulic kit / PATENTED
 Safety device for a controlled rewinding of the hose.
 Restrains the hose in case of accidental releases, lowering risks for the operator.
Patent no. 0001426967

