

Automatic rewind, spring-driven hose reel, **adjustable arms series**, in painted steel or in stainless steel AISI 304, suitable for applications with high delivery rates and for hoses of max 20 m length (Ø hose 1 1/4") or max. 15 m length (Ø hose 1 1/2").

The hose reel is supplied without hoses and can be used with hoses for the supply of oils, diesel, compressed air and water. From the inlet swivel joint the fluid flows through an interchangeable hose connection adapter assembly on which the hose is mounted (standard version galvanized steel, available **on demand also in stainless steel AISI 304 or AISI 316**).

Please see catalogue pages 220 and 221 for the selection of the required hoses.

On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9031/HB)!



On demand the stainless steel hose reels can also be supplied in accordance with directive ATEX 2014/34/EU – group II – category 2.

Art.no.	Material	Max working pressure	Connection threads IN - OUT	Internal ø swivel joint	Max diameter hose	Max length hose	Included swivel joint	Dimensions (A-B-C) (mm)	Spool width (F)	Weight
9031	Painted steel	20 bar	1 1/2" (M) - 1 1/2" (F)	25 mm	1 1/4"	8 m	9980	430x500x490	200 mm	18 kg
9038						20 m	9978	590x670x670	400 mm	49 kg
9039				32 mm	1 1/2"	15 m	9899			
9531	Stainless steel AISI 304			25 mm	1 1/4"	8 m	9870	430x500x490	200 mm	18 kg
9538						20 m	9861	590x670x670	400 mm	49 kg
9539				32 mm	1 1/2"	15 m	9791			

OPTIONAL

HB Spring brake hydraulic kit / PATENTED
Safety device for a controlled rewinding of the hose.

Restrains the hose in case of accidental releases, lowering risks for the operator.

Patent no. 0001426967

