


Automatic rewind, spring-driven hose reel, **heavy duty series**, in painted steel or in stainless steel AISI 304, suitable for hoses of max 25 m length. The art.no. 9036 is equipped with a twin spring for a convenient hose rewind. The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, diesel, compressed air and water at low pressure. Please see catalogue pages 220 and 221 for the selection of the required hoses. On demand the hose reels can also be supplied with a **spring brake kit** (see information at the end of this page!); please add suffix **"/HB"** to the article number (f. ex. 9034/HB)!



Art.no. **9768**
Art.no. **9769**



Art.no. **9764**
Art.no. **9765**



Art.no.	Material	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 3/4" - 1"	Suitable pivoting wall bracket	Included swivel joint	Dimensions (A-B-C) (mm)	Spool width (F)	Weight
9030	Painted steel	100 bar	1" (M) - 1" (F)	20 mm	1"	12 m - 8 m	9768	9986	295x530x500	150 mm	21 Kg
9034						18 m - 15 m	9769		440x530x500	300 mm	24 Kg
9036						25 m	-		500x530x540	400 mm	36 Kg
9529	Stainless steel AISI 304	100 bar	1" (M) - 1" (F)	20 mm	1"	12 m - 8 m	9765	9986	295x530x500	150 mm	21 Kg
9525						18 m - 15 m	9764		440x530x500	300 mm	24 Kg
9536						25 m	-		500x530x540	400 mm	36 Kg



OPTIONAL

HB Spring brake hydraulic kit / PATENTED

Safety device for a controlled rewinding of the hose.

Restrains the hose in case of accidental releases, lowering risks for the operator.

Patent no. 0001426967

