

Art.no. **9251 - 9252 - 9253 - 9256**

Manual, hand crank hose reel, **LS series**, in painted steel, suitable for hoses of max 50 m length in 1/2".

The hose reel is supplied without hoses and can be used with hoses for the supply of oils, antifreeze, grease, compressed air and water at low and high pressure.

Please see catalogue pages 268 and 269 for the selection of the required hoses.




Art.no. **9767**
Art.no. **9768**

Art.no. **9254**

Manual, hand crank hose reel, **LS series**, in painted steel, suitable for hoses of max 12 m length in 1" or max 15 m length in 3/4".

The hose reel is supplied without hoses and can be used with hoses for the supply of diesel, compressed air and water at low pressure.

Please see catalogue pages 268 and 269 for the selection of the required hoses.




Art.no. **9773**

Art.no. **9255**

Manual, hand crank hose reel, **LS series**, in painted steel, suitable for hoses of max 20 m length in 1" or max 25 m length in 3/4".

The hose reel is supplied without hoses and can be used with hoses for the supply of diesel, compressed air and water at low pressure.

Please see catalogue pages 268 and 269 for the selection of the required hoses.



Art.no.	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 1/4" - 3/8" - 1/2"	Spool width	Suitable pivoting wall bracket	Included swivel joint	Weight	Dimensions (LxWxH) (mm)
9251	600 bar	1/2" (M) - 1/2" (F)	10 mm	1/2"	25 m - 20 m - 15 m	120 mm	9767	9951	8 kg	280 x 530 x 480
9252					50 m - 35 m - 25 m	150 mm	9768		9 kg	320 x 530 x 480
9253					70 m - 50 m - 35 m	200 mm	9773		12 kg	
9256					100 m - 70 m - 50 m	400 mm	-		15 kg	

Art.no.	Max working pressure	Connection threads IN - OUT	Internal diameter swivel joint	Max diameter hose	Max length hose 3/4" - 1"	Spool width	Suitable pivoting wall bracket	Included swivel joint	Weight	Dimensions (LxWxH) (mm)
9254	100 bar	1" (M) - 1" (M)	20 mm	1"	15 m - 12 m	200 mm	9773	9986	12 kg	320 x 530 x 480
9255					25 m - 20 m	400 mm	-		15 kg	480 x 530 x 480

