

The **FLEXBIMEC** oil pump range is completed by the industrial pump series **"Power Bull"** with high delivery pumps for the supply of fluid lubricants in demanding conditions. These pumps are particularly recommended for the distribution of medium or high viscosity oils in applications or pipeworks where a simultaneous supply in different distribution points at high pressure and high delivery is required. The elevated quality of the used materials and the innovative constructional concept of the pneumatic motors of this line assure the following characteristics and advantages:

- Efficiency of a constant flow,
- Low noise level,
- Limited number of piston strokes,
- Low vibrations,
- Easy maintenance and interchangeability of components.

Series Tapir



Art.no. 2012 Art.no. 2013 Art.no. 2016

Industrial pump series "Power Bull" Single acting models



Art.no. 2055 Art.no. 2056 Art.no. 2096 Art.no. 2097 Art.no. 2098

Industrial pump series "Power Bull" Double acting models



Art.no. 2092 Art.no. 2093 Art.no. 2094

Art.no.	Ratio	Delivery			
2012	6:1	32 l/min			
2013	2:1	48 l/min			
2014	5:1	18 l/min			
2015	5:1	18 l/min			
2016	6:1	32 l/min			

Art.no.	Ratio	Delivery			
2055	10:1	27 l/min			
2056	16:1	15 l/min			
2096	5:1	42 l/min			
2097	10:1	34 l/min			
2098	1.5:1	122 l/min			

Art.no.	Ratio	Delivery			
2057	10:1	27 l/min			
2058	16:1	15 l/min			
2088	3,5:1	64 l/min			
2091	6:1	42 l/min			
2092	7:1	40 l/min			
2093	4:1	67 l/min			
2094	6:1	55 l/min			

These pumps are recommended

- to achieve high deliveries in the use with low viscosity fluids (art.no. 2013),
- for the use with low and medium viscosity fluids at pumping distances of more than 300 m,
- for the use with high viscosity fluids at long pumping distances (art. nos. 2012 and 2016)
- for simultaneous fluid supplies.

See page 70

These pumps are recommended

- to achieve very high deliveries in the use with low viscosity fluids (art. no. 2098),
- for the use with low and medium viscosity fluids at pumping distances of more than 300 m,
- for the use with high viscosity fluids at long pumping distances (art. nos. 2055, 2056, 2096, 2097),
- for simultaneous fluid supplies.

See page 72

These pumps are recommended

- to achieve high deliveries in the use with low viscosity fluids,
- for the use with low and medium viscosity fluids at pumping distances of more than 300 m,
- for the use with high viscosity fluids at long pumping distances,
- for simultaneous fluid supplies.

See pages 71-73

Legend

Oil SAE 0/40		Oil SAE 90		Oil SAE 240		Waste oil		Antifreeze	
--------------	--	------------	--	-------------	--	-----------	--	------------	--