

Art.no. 2717

Electronic oval gears flow meter with pulse transmitter, body in IXEF, including a stainless steel 24 VDC - solenoid valve. Suitable for the use with water-based fluids and AdBlue® (DEF). Appropriate to the use in combination with electronic oil monitoring systems by the use of an external receiver.



Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Number of pulses	Weight
2717	1/2" BSP (M)	35 l/min	+5°C / +70°C	30 bar (435 psi)	+ / - 0.5%	78/l	0.6 kg

Art.no. 2954

Electronic oval gears flow meter with pulse transmitter, suitable for oil and antifreeze. Appropriate to the use in combination with electronic oil monitoring systems by the use of an external receiver.

Art.no. 2716

Electronic oval gears flow meter with pulse transmitter, body in IXEF. Suitable for the use with water-based fluids and AdBlue® (DEF).



Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Number of pulses	Weight
2954	1/2" BSP (M)	20 l/min	+5°C / +50°C	70 bar (1015 psi)	+ / - 0.5%	78/l	0.6 Kg
2716				5 bar (72 psi)			0.4 Kg

Art.no. 2853

Electronic oval gears high delivery flow meter with pulse transmitter, suitable for oil, diesel and antifreeze. Appropriate to the use in combination with electronic oil monitoring systems by the use of an external receiver.



Art. no.	Connections	Max flow	Operating temperature range	Max working pressure	Accuracy	Number of pulses	Weight
2853	1" BSP (F)	70 l/min	+ 5°C / +50°C	50 bar (725 psi)	+ / - 0.5%	39/l	1.6 kg