

Waste oil suction units which allow to suck out the oil with appropriate suction probes or suction adapters inserted in the dip-stick tube of the motor by means of a pneumatic rotary or piston pump or by means of an electric pump. The oil suction process is also possible with these units if the oil temperature is equal to the ambient temperature (unless in case of low temperatures).

## Art.no. 3020

OIL BLITZ – Mobile waste oil suction unit, composed of a pneumatic rotary gear pump, suction hose, kit of suction probes in different diameters (see on page 153!), suction adapters, storage bowl, two wheels trolley in galvanized steel and 20 l – capacity plastic can for collection of the sucked oil.

Can be used also to suck out diesel from vehicle fuel tanks.



| Art. no.    | Max vacuum | Pressure compressed air | Compression ratio | Consumption compressed air | Outlet pressure | Weight | Dimensions (LxWxH) (mm) |
|-------------|------------|-------------------------|-------------------|----------------------------|-----------------|--------|-------------------------|
| <b>3020</b> | 0.8 bar    | 1 - 4 bar               | 1:1               | 180 l/min                  | 4 bar           | 17 kg  | 410x420x910             |



## Art.no. 3172

Waste oil suction system such as art. no. 3099 (see on page 151!), but mounted on a heavy duty trolley, consisting of 1:1 - pneumatic piston pump art. no. 2047FVN, pressure regulator and air filter with moisture separator, kit of suction probes in different diameters and suction adapters (see on page 153!), 3 m - suction hose with shut-off valve and connections, vacuumeter for the control of the suction process and 1.6 m - discharge hose with curved outlet tube.

On demand alternatively also a discharge hose with suitable connection to a pipework can be supplied.



| Art. no.    | Max vacuum  | Pressure compressed air | Compression ratio | Consumption compressed air | Outlet pressure | Weight | Dimensions (LxWxH) (mm) |
|-------------|-------------|-------------------------|-------------------|----------------------------|-----------------|--------|-------------------------|
| <b>3172</b> | 0,8/1,0 bar | 2 - 4 bar               | 1:1               | 120 l/min                  | 4 bar (58 psi)  | 42 Kg  | 790x900x1400            |



## Art.no. 3018

OIL BLITZ – Mobile waste oil suction unit, composed of an electric rotary gear pump, suction hose, kit of suction probes in different diameters (see on page 153!), suction adapters, storage bowl, two wheels trolley in galvanized steel and 20 l – capacity plastic can for collection of the sucked oil.

Can be used also to suck out diesel from vehicle fuel tanks.



| Art. no.    | Voltage         | Power   | Protection category | Max vacuum | Weight | Dimensions (LxWxH) (mm) |
|-------------|-----------------|---------|---------------------|------------|--------|-------------------------|
| <b>3018</b> | 230 VAC – 50 Hz | 0.53 Kw | IP 55               | 0.8 bar    | 17 kg  | 410x420x910             |

