


Pneumatic brake bleeding unit with two chambers which are hermetically separated by an elastic diaphragm. One chamber of the container contains the brake fluid, the other chamber serves as reservoir for the compressed air. Max. working pressure 2 bar. The diaphragm permits to separate the brake fluid and the compressed air, avoiding like that the risk of an emulsion.

Art.no. **3406**

Pneumatic brake bleeding unit, with pressure regulator, 3 m – spiral fluid supply hose, for the bleeding of brakes and clutches, including those with ABS. Container capacity: 9 l.

The unit includes also the following accessories:

- 2 plastic jerrycans for the collection of the brake fluid, art. no. 3485,
- 2 plastic bleeding hoses, art. no. 3481,
- 1 plastic funnel, art. no. 3486.



Art.no.	Weight	Dimensions (LxWxH) (mm)
3406	8.5 Kg	270x340x700



Art.no. **3495**

Mobile brake bleeding unit, consisting of:

- trolley with 4 castors, art. no. 4357,
- pneumatic brake bleeding unit, art. no. 3406,
- kit of bleeding adapters for passenger cars and trucks, art. no. 3490
- 2 plastic jerrycans for the collection of the brake fluid, art. no. 3485,
- 2 plastic bleeding hoses, art. no. 3481,
- 1 plastic funnel, art. no. 3486.



Art.no.	Weight	Dimensions (LxWxH) (mm)
3495	30 Kg	500x610x1130

