

Ø 1"

Ø 1" 1/4

Art.no. **2754**

Electronic oval gears high delivery flow meter for oil, **series Oil Neptune HFlow**, with control gun Ø 1", trigger guard, cartridge filter, rigid outlet Ø 20 mm, automatic anti-drip nozzle and 1" BSP (M) inlet swivel.

This high volume series allows to accelerate the oil supplies by the use of a flow meter that guarantees high accuracy measurement even at high flow rates.



Art.no. **2751**
Art.no. **2752**

Art.no. **2751**

Electronic oval gears high delivery flow meter for oil, **series Oil Neptune HFlow**, suitable for inline applications, connections 1" BSP (F).

Art.no. **2752**

Electronic oval gears high delivery flow meter for oil, **series Oil Neptune HFlow**, suitable for inline applications, connections 1" 1/4 BSP (F).

Art.no. **2755**

Electronic oval gears high delivery flow meter for oil, **series Oil Neptune HFlow**, with control gun Ø 1", trigger guard, cartridge filter, flexible rubber outlet Ø 1", automatic anti-drip nozzle and 1" BSP (M) inlet swivel.

Art.no.	2751	2752	2754	2755
Connections	1" BSP (F)	1" 1/4 BSP (F)	1" BSP (M)	
Flow rate min – max	20 - 100 l/min	20 - 150 l/min	20 - 100 l/min	
Temperature	+ 5°C / + 50°C			
Max pressure	40 bar (580 psi)		100 bar (1450 psi)	
Precision	± 1%			
Total max (resettable)	9999 l			
Total max (non-resettable)	9999 l			
Voltage	3 x 1.5 V			
Weight	1.6 kg	1.8 kg	3.9 kg	

Not approved for fiscal transactions.