



400 SERIES - ASG1 Ø Disc 434 mm - Spool 130 mm - Drum 250 mm

	Art.no. WITHOUT HOSE GUIDE	Max. pressure joint	Connection threads IN - OUT	Spring	Max diameter hose	Max length hose (m)	Pivoting wall bracket	Swivel joint*
PAINTED STEEL	ASGF4213150	600 bar **	1/2"(M)-1/2"(F)	15m	1/4"- 3/8"-1/2"	15	9767	9951
	ASGF4213200			20m	1/4"- 3/8" 1/2"	20		
	ASGF4213250			25m	1/4"- 3/8"	25		
	ASGF4213151	100 bar	1"(M)-3/4"(F)	15m	3/4" 1"	12 6	9760	9986
AISI 304 STAINLESS STEEL	ASGX4213150	200 bar **	1/2"(M)-1/2"(F)	15m	1/4"- 3/8"-1/2"	15		
	ASGX4213200			20m	1/4"- 3/8" 1/2"	20		
	ASGX4213250			25m	1/4"- 3/8"	25		
	ASGX4213151	100 bar	1"(M)-3/4"(F)	15m	3/4" 1"	12 6		

400 SERIES - ASG2 Ø Disc 434 mm - Spool 195 mm - Drum 250 mm

	Art.no. WITHOUT HOSE GUIDE	Max. pressure joint	Connection threads IN - OUT	Spring	Max diameter hose	Max length hose (m)	Pivoting wall bracket	Swivel joint*
PAINTED STEEL	ASGF4219200	600 bar **	1/2"(M)-1/2"(F)	20m	1/4" - 3/8"-1/2"	20	15001	9951
	ASGF4219250			25m	1/4" - 3/8"-1/2"	25		
	ASGF4219151	100 bar	1"(M)-3/4"(F)	15m	3/4" 1"	15 10	20001	9986
AISI 304 STAINLESS STEEL	ASGX4219200	200 bar **	1/2"(M)-1/2"(F)	20m	1/4" - 3/8"-1/2"	20		
	ASGX4219250			25m	1/4" - 3/8"-1/2"	25		
	ASGX4219151	100 bar	1"(M)-3/4"(F)	15m	3/4" 1"	15 10		

400 SERIES - ASG3 Ø Disc 434 mm - Spool 260 mm - Drum 250 mm

	Art.no. WITHOUT HOSE GUIDE	Max. pressure joint	Connection threads IN - OUT	Spring	Max diameter hose	Max length hose (m)	Pivoting wall bracket	Swivel joint*
PAINTED STEEL	ASGF4226201	100 bar	1"(M)-3/4"(F)	20m	3/4"	20	15002	9986
	ASGF4226151			15m	1"	15		
AISI 304 STAINLESS STEEL	ASGX4226201	100 bar	1"(M)-3/4"(F)	20m	3/4"	20	20002	9986
	ASGX4226151			15m	1"	15		

*) The reels in painted steel are equipped with mineral oil compatible swivel joint gaskets. The hose reels in stainless steel come with water-compatible Viton® swivel joint gaskets. See pages 263-265 for the complete range of swivel joints with gaskets compatible with other liquids.

**) When ordering, specify whether or not the application implies the use of low pressure hoses (see page 266 regarding the splitting of the roller).

DIMENSIONS AND PACKAGING

Art.no.	D (mm)	F (mm)	E (mm)	A-B-C (mm)	Packaging dimensions (mm)	Weight (kg)
ASG1	434	130	250	212x474x522	600x370x620	15
ASG2	434	195	250	276x474x523	600x370x620	19
ASG3	434	260	250	339x474x523	560x490x560	21

