



500 SERIES - ASG4 Ø Disc 540 mm - Spool 130 mm - Drum 250 mm

	Art.no. WITHOUT HOSE GUIDE	Max. pressure joint	Connection threads IN - OUT	Spring	Max diameter hose	Max length hose (m)	Pivoting wall bracket	Swivel joint*
PAINTED STEEL	ASGF5213200	600 bar **	1/2"(M)-1/2"(F)	20m	1/4"- 3/8"-1/2"	20	9767	9951
	ASGF5213250			25m		25		
	ASGF5213201	100 bar	1"(M)-3/4"(F)	20m	3/4" 1"	20 12		9986
AISI 304 STAINLESS STEEL	ASGX5213200	200 bar **	1/2"(M)-1/2"(F)	20m	1/4"- 3/8"-1/2"	20	9760	9963
	ASGX5213250			25m		25		
	ASGX5213201	100 bar	1"(M)-3/4"(F)	20m	3/4" 1"	20 12		9986

500 SERIES - ASG5 Ø Disc 540 mm - Spool 195 mm - Drum 250 mm

	Art.no. WITHOUT HOSE GUIDE	Max. pressure joint	Connection threads IN - OUT	Spring	Max diameter hose	Max length hose (m)	Pivoting wall bracket	Swivel joint*
PAINTED STEEL	ASGF521925H501	100 bar	1"(M)-3/4"(F)	25mH50	3/4"	25	15001 	9986
	20m			3/4"	20			
				1"	18			
AISI 304 STAINLESS STEEL	ASGX521925H501	100 bar	1"(M)-3/4"(F)	25mH50	3/4"	25	20001 	9986
	20m			3/4"	20			
				1"	18			

500 SERIES - ASG6 Ø Disc 540 mm - Spool 260 mm - Drum 250 mm

	Art.no. WITHOUT HOSE GUIDE	Max. pressure joint	Connection threads IN - OUT	Spring	Max diameter hose	Max length hose (m)	Pivoting wall bracket	Swivel joint*
PAINTED STEEL	ASGF522625H501	100 bar	1"(M)-3/4"(F)	25mH50	3/4" - 1"	25	15002	9986
AISI 304 STAINLESS STEEL	ASGX522625H501	100 bar	1"(M)-3/4"(F)	25mH50	3/4" - 1"	25	20002	9986

*) The reels in painted steel are equipped with mineral oil compatible swivel joint gaskets. The hose reels in stainless steel come with water-compatible Viton® swivel joint gaskets. See pages 263-265 for the complete range of swivel joints with gaskets compatible with other liquids.

**) When ordering, specify whether or not the application implies the use of low pressure hoses (see page 266 regarding the splitting of the roller).

DIMENSIONS AND PACKAGING

Art.no.	D (mm)	F (mm)	E (mm)	A-B-C (mm)	Packaging dimensions (mm)	Weight (kg)
ASG4	540	130	250	212x565x625	700x370x700	20
ASG5	540	195	250	281x565x626	700x420x660	22
ASG6	540	260	250	346x565x626	700x420x660	23