



500 SERIES - ASG7 Ø Disc 540 mm - Spool 130 mm - Drum 335 mm

	Art.no. WITHOUT HOSE GUIDE	Max. pressure joint	Connection threads IN - OUT	Spring	Max diameter hose	Max length hose (m)	Pivoting wall bracket	Swivel joint*
PAINTED STEEL	ASGF5313200	600 bar **	1/2"(M)-1/2"(F)	20m	1/4"- 3/8"-1/2"	20	9767	9951
	ASGF5313350			35m		35		
	ASGF5313201	100 bar	1"(M)-3/4"(F)	20m	3/4" 1"	20 12	9767	9986
AISI 304 STAINLESS STEEL	ASGX5313200	200 bar **	1/2"(M)-1/2"(F)	20m	1/4"- 3/8"-1/2"	20	9760	9963
	ASGX5313350			35m		35		
	ASGX5313201	100 bar	1"(M)-3/4"(F)	20m	3/4" 1"	20 12	9760	9986

500 SERIES - ASG8 Ø Disc 540 mm - Spool 195 mm - Drum 335 mm

	Art.no. WITHOUT HOSE GUIDE	Max. pressure joint	Connection threads IN - OUT	Spring	Max diameter hose	Max length hose (m)	Pivoting wall bracket	Swivel joint*
PAINTED STEEL	ASGF5319350	600 bar **	1/2"(M)-1/2"(F)	35m	1/4"- 3/8"-1/2"	35	15001	9951
	ASGF5319351					30		
	ASGF5319201	100 Bar	1"(M)-3/4"(F)	20m	3/4" 1"	20 18	15001	9986
AISI 304 STAINLESS STEEL	ASGX5319350	200 bar **	1/2"(M)-1/2"(F)	35m	1/4"- 3/8"-1/2"	35	20001	9963
	ASGX5319351					30		
	ASGX5319201	100 Bar	1"(M)-3/4"(F)	20m	3/4" 1"	20 18	20001	9986

500 SERIES - ASG9 Ø Disc 540 mm - Spool 260 mm - Drum 335 mm

	Art.no. WITHOUT HOSE GUIDE	Max. pressure joint	Connection threads IN - OUT	Spring	Max diameter hose	Max length hose (m)	Pivoting wall bracket	Swivel joint*
PAINTED STEEL	ASGF5326350	600 bar **	1/2"(M)-1/2"(F)	35m	1/4"- 3/8"-1/2"	35	15002	9951
	ASGF5326351							
	ASGF5326351	100 bar	1"(M)-3/4"(F)		3/4" 1"	25	15002	9986
AISI 304 STAINLESS STEEL	ASGX5326350	200 bar **	1/2"(M)-1/2"(F)	35m	1/4"- 3/8"-1/2"	35	20002	9963
	ASGX5326351							
	ASGX5326351	100 bar	1"(M)-3/4"(F)		3/4" 1"	25	20002	9986

*) The reels in painted steel are equipped with mineral oil compatible swivel joint gaskets. The hose reels in stainless steel come with water-compatible Viton® swivel joint gaskets. See pages 263-265 for the complete range of swivel joints with gaskets compatible with other liquids.

**) When ordering, specify whether or not the application implies the use of low pressure hoses (see page 266 regarding the splitting of the roller).

DIMENSIONS AND PACKAGING

Art.no.	D (mm)	F (mm)	E (mm)	A-B-C (mm)	Packaging dimensions (mm)	Weight (kg)
ASG7	540	130	335	281x565x626	700x420x660	20
ASG8	540	195	335	281x565x626	700x420x660	22
ASG9	540	260	335	346x565x626	700x420x660	23