

WITH
HOSE GUIDE



ORION HEAVY DUTY
with hose guide

WHEELED VERSION COMPOSED OF:

- Nr. 2 wheels Ø 200 mm
- Nr. 2 adjustable handles.

To order this model
add MR to the reel's code
(e.g. OPF52190MR).
(See tables on page 248)

WITHOUT
HOSE GUIDE



ORION HEAVY DUTY
without hose guide

ORION EASY

MANUAL HOSE REELS

WITHOUT
HOSE GUIDE



ORION EASY wheeled hose reel with reduced effort system with **3:1 rapport** and reel rotation lock mechanism. The EASY model comes with wheels.

EASY 400 SERIES - OE1 Ø Disc 434 mm - Spool 400 mm - Drum 260 mm

	Art.no. WITHOUT HOSE GUIDE	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	OEF42400	600 bar **	1/2"(M)-1/2"(F)	1/4"	150	9951
				3/8"	100	
				1/2"	80	
	OEF42401	100 bar	1"(M)-3/4"(F)	3/4"	42	9986
				1"	25	
AISI 304 STAINLESS STEEL	OEX42400	200 bar **	1/2"(M)-1/2"(F)	1/4"	150	9963
				3/8"	100	
				1/2"	80	
	OEX42401	100 bar	1"(M)-3/4"(F)	3/4"	42	9986
				1"	25	

EASY 500 SERIES - OE2 Ø Disc 540 mm - Spool 400 mm - Drum 335 mm

	Art.no. WITHOUT HOSE GUIDE	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	OEF53400	600 bar **	1/2"(M)-1/2"(F)	1/4"	200	9951
				3/8"	140	
				1/2"	100	
	OEF53401	100 bar	1"(M)-3/4"(F)	3/4"	50	9986
				1"	35	
AISI 304 STAINLESS STEEL	OEX53400	200 bar **	1/2"(M)-1/2"(F)	1/4"	200	9963
				3/8"	140	
				1/2"	100	
	OEX53401	100 bar	1"(M)-3/4"(F)	3/4"	50	9986
				1"	35	

*) The reels in painted steel are equipped with mineral oil compatible swivel joint gaskets. The hose reels in stainless steel come with water-compatible Viton® swivel joint gaskets. See pages 263-265 for the complete range of swivel joints with gaskets compatible with other liquids.

**) When ordering, specify whether or not the application implies the use of low pressure hoses (see page 266 regarding the splitting of the roller).

DIMENSIONS AND PACKAGING

Art.no.	D (mm)	F (mm)	E (mm)	A-B-C (mm)	Packaging dimensions (mm)	Weight (kg)
OE1	434	400	250	665x542x523	600x500x700	24
OE2	540	400	250	665x542x677	600x500x700	25

