


500 SERIES - S4 Ø Disc 540 mm - Spool 130 mm - Drum 250 mm

	Art.no. 12 Vdc	Art.no. 24 Vdc	Art.no. ID HYDRAULIC	Art.no. PNEUMATIC	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	SF1252130	SF2452130	SFID52130	SFPN52130	600 bar **	1/2"(M) 1/2"(F)	1/4"	80	9951
							3/8"	60	
							1/2"	45	
	SF1252131	SF2452131	SFID52131	SFPN52131	100 bar	1"(M)-3/4"(F)	3/4"	22	9986
							1"	12	
AISI 304 STAINLESS STEEL	SX1252130	SX2452130	SXID52130	SXPNS2130	200 bar **	1/2"(M) 1/2"(F)	1/4"	80	9963
							3/8"	60	
							1/2"	45	
	SX1252131	SX2452131	SXID52131	SXPNS2131	100 bar	1"(M)-3/4"(F)	3/4"	22	9986
							1"	12	

500 SERIES - S5 Ø Disc 540 mm - Spool 195 mm - Drum 250 mm

	Art.no. 12 Vdc	Art.no. 24 Vdc	Art.no. ID HYDRAULIC	Art.no. PNEUMATIC	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	SF1252190	SF2452190	SFID52190	SFPN52190	600 bar **	1/2"(M) 1/2"(F)	1/4"	120	9951
							3/8"	90	
							1/2"	70	
	SF1252191	SF2452191	SFID52191	SFPN52191	100 bar	1"(M)-3/4"(F)	3/4"	35	9986
							1"	18	
AISI 304 STAINLESS STEEL	SX1252190	SX2452190	SXID52190	SXPNS2190	200 bar **	1/2"(M) 1/2"(F)	1/4"	120	9963
							3/8"	90	
							1/2"	70	
	SX1252191	SX2452191	SXID52191	SXPNS2191	100 bar	1"(M)-3/4"(F)	3/4"	35	9986
							1"	18	

500 SERIES - S6 Ø Disc 540 mm - Spool 260 mm - Drum 250 mm

	Art.no. ID HYDRAULIC	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	SFID52260	600 bar **	1/2"(M) 1/2"(F)	1/4"	180	9951
				3/8"	115	
				1/2"	90	
AISI 304 STAINLESS STEEL	SXID52260	200 bar **	1/2"(M) 1/2"(F)	1/4"	180	9963
				3/8"	115	
				1/2"	90	

ELECTRIC MOTOR FOR SIRIO

Motor	Voltage	Absorption	Power output	Rpm
MS12V	12Vdc	4.5A	55W	4500
MS24V	24Vdc	3.75A	90W	3000

DIMENSIONS AND PACKAGING

Art.no.	D (mm)	F (mm)	E (mm)	A-B-C (mm)	Packaging dimensions (mm)	Weight (kg)
S4	540	130	250	358x594x632	670x800x900	26
S5	540	195	250	426x598x632	670x800x900	28
S6	540	260	250	504x604x632	670x800x900	32

*) The reels in painted steel are equipped with mineral oil compatible swivel joint gaskets. The hose reels in stainless steel come with water-compatible Viton® swivel joint gaskets. See pages 263-265 for the complete range of swivel joints with gaskets compatible with other liquids.

**) When ordering, specify whether or not the application implies the use of low pressure hoses (see page 266 regarding the splitting of the roller).

