


500 SERIES - G1 Ø Disc 540 mm - Spool 195 mm - Drum 250 mm

	Art.no. 12 Vdc	Art.no. 24 Vdc	Art.no. 230 Vac	Art.no. WITHOUT POWER SUPPLY	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	GF1252190	GF2452190	GF2352190	GFSGA52190	600 bar	1/2"(M) 1/2"(F)	1/4"	130	9951
							3/8"	85	
							1/2"	65	
	GF1252191	GF2452191	GF2352191	GFSGA52191	100 bar	1"(M)- 3/4"(F)	3/4"	30	9986
							1"	18	
AISI 304 STAINLESS STEEL	GX1252190	GX2452190	GX2352190	GXSGA52190	200 bar	1/2"(M) 1/2"(F)	1/4"	130	9963
							3/8"	85	
							1/2"	65	
	GX1252191	GX2452191	GX2352191	GXSGA52191	100 bar	1"(M)- 3/4"(F)	3/4"	30	9986
							1"	18	

500 SERIES - G2 Ø Disc 540 mm - Spool 260 mm - Drum 250 mm

	Art.no. 12 Vdc	Art.no. 24 Vdc	Art.no. 230 Vac	Art.no. WITHOUT POWER SUPPLY	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	GF1252260	GF2452260	GF2352260	GFSGA52260	600 bar **	1/2"(M) 1/2"(F)	1/4"	180	9951
							3/8"	115	
							1/2"	90	
	GF1252261	GF2452261	GF2352261	GFSGA52261	100 bar	1"(M)- 3/4"(F)	3/4"	40	9986
							1"	25	
AISI 304 STAINLESS STEEL	GX1252260	GX2452260	GX2352260	GXSGA52260	200 bar **	1/2"(M) 1/2"(F)	1/4"	180	9963
							3/8"	115	
							1/2"	90	
	GX1252261	GX2452261	GX2352261	GXSGA52261	100 bar	1"(M)- 3/4"(F)	3/4"	40	9986
							1"	25	

600 SERIES - G3 Ø Disc 600 mm - Spool 260 mm - Drum 335 mm

	Art.no. 12 Vdc	Art.no. 24 Vdc	Art.no. 230 Vac	Art.no. WITHOUT POWER SUPPLY	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	GF1263260	GF2463260	GF2363260	GFSGA63260	600 bar **	1/2"(M) 1/2"(F)	1/4"	200	9951
							3/8"	150	
							1/2"	110	
	GF1263261	GF2463261	GF2363261	GFSGA63261	100 bar	1"(M)- 3/4"(F)	3/4"	55	9986
							1"	32	
	GF1263262	GF2463262	GF2363262	GFSGA63262	20 bar	1 1/4"(M)- 1 1/4"(M)	1 1/4"	22	9982
AISI 304 STAINLESS STEEL	GF1263263	GF2463263	GF2363263	GFSGA63263	20 bar	1 1/4"(M)- 1 1/2"(M)	1 1/2"	15	9983
	GX1263260	GX2463260	GX2363260	GXSGA63260	200 bar **	1/2"(M) 1/2"(F)	1/4"	200	9963
							3/8"	150	
							1/2"	110	
	GX1263261	GX2463261	GX2363261	GXSGA63261	100 bar	1"(M)- 3/4"(F)	3/4"	55	9986
							1"	32	
	GX1263262	GX2463262	GX2363262	GXSGA63262	20 bar	1 1/4"(M)- 1 1/4"(M)	1 1/4"	22	9982
	GX1263263	GX2463263	GX2363263	GXSGA63263	20 bar	1 1/4"(M)- 1 1/2"(M)	1 1/2"	15	9983

*) The reels in painted steel are equipped with mineral oil compatible swivel joint gaskets. The hose reels in stainless steel come with water-compatible Viton® swivel joint gaskets. See pages 263-265 for the complete range of swivel joints with gaskets compatible with other liquids.

**) When ordering, specify whether or not the application implies the use of low pressure hoses (see page 266 regarding the splitting of the roller).

DIMENSIONS AND PACKAGING

Art.no.	D (mm)	F (mm)	E (mm)	A-B-C (mm)	Packaging dimensions (mm)	Weight (kg)
G1	540	195	250	385x670x834	670x800x900	56
G2	540	260	250	450x670x834	670x800x900	63
G3	600	260	335	450x730x894	670x800x900	68