



Manual hose guide.
Standard



Automatic hose guide.
Optional



Manual hose guide.
Standard

MOTOR DRIVEN SERIES - T4 Ø Disc 680 mm - Spool 400 mm - Drum 250 mm

	Art.no. 12 Vdc	Art.no. 24 Vdc	Art.no. 230 Vac	Art.no. WITHOUT POWER SUPPLY	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	TF1262401	TF2462401	TF2362401	TFSGA62401	100 bar	1"(M)-3/4"(F)	3/4"	130	9986
							1"	75	
AISI 304 STAINLESS STEEL	TX1262401	TX2462401	TX2362401	TXSGA62401	100 bar	1"(M)-3/4"(F)	3/4"	130	9986
							1"	75	

MOTOR DRIVEN SERIES - T5 Ø Disc 680 mm - Spool 400 mm - Drum 335 mm

	Art.no. 12 Vdc	Art.no. 24 Vdc	Art.no. 230 Vac	Art.no. WITHOUT POWER SUPPLY	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	TF1263401	TF2463401	TF2363401	TFSGA63401	100 bar	1"(M)-3/4"(F)	3/4"	100	9986
	TF1263402	TF2463402	TF2363402	TFSGA63402	20 bar	1 1/4"(M)- 1 1/4"(M)	1 1/4"	50	
	TF1263403	TF2463403	TF2363403	TFSGA63403		1 1/4"(M)- 1 1/2"(M)	1 1/2"	30	9983
AISI 304 STAINLESS STEEL	TX1263401	TX2463401	TX2363401	TXSGA63401	100 bar	1"(M)-3/4"(F)	3/4"	100	9986
	TX1263402	TX2463402	TX2363402	TXSGA63402	20 bar	1 1/4"(M)- 1 1/4"(M)	1 1/4"	50	
	TX1263403	TX2463403	TX2363403	TXSGA63403		1 1/4"(M)- 1 1/2"(M)	1 1/2"	30	9983

MOTOR DRIVEN SERIES - T6 Ø Disc 680 mm - Spool 600 mm - Drum 335 mm

	Art.no. 12 Vdc	Art.no. 24 Vdc	Art.no. 230 Vac	Art.no. WITHOUT POWER SUPPLY	Max. pressure joint	Connection threads IN - OUT	Max diameter hose	Max length hose (m)	Swivel joint*
PAINTED STEEL	TF1263601	TF2463601	TF2363601	TFSGA63601	100 bar	1"(M)-3/4"(F)	3/4"	180	9986
	TF1263602	TF2463602	TF2363602	TFSGA63602	20 bar	1 1/4"(M)- 1 1/4"(M)	1 1/4"	75	
	TF1263603	TF2463603	TF2363603	TFSGA63603		1 1/4"(M)- 1 1/2"(M)	1 1/2"	50	9983
AISI 304 STAINLESS STEEL	TX1263601	TX2463601	TX2363601	TXSGA63601	100 bar	1"(M)-3/4"(F)	3/4"	180	9986
	TX1263602	TX2463602	TX2363602	TXSGA63602	20 bar	1 1/4"(M)- 1 1/4"(M)	1 1/4"	75	
	TX1263603	TX2463603	TX2363603	TXSGA63603		1 1/4"(M)- 1 1/2"(M)	1 1/2"	50	9983

*) The reels in painted steel are equipped with mineral oil compatible swivel joint gaskets. The hose reels in stainless steel come with water-compatible Viton® swivel joint gaskets. See pages 263-265 for the complete range of swivel joints with gaskets compatible with other liquids.

**) When ordering, specify whether or not the application implies the use of low pressure hoses (see page 266 regarding the splitting of the roller).

DIMENSIONS AND PACKAGING

Art.no.	D (mm)	F (mm)	E (mm)	A-B-C (mm)	Packaging dimensions (mm)	Weight (kg)
T4	680	400	250	586x730x894	670x800x900	74
T5	680	400	335	586x730x894	670x800x900	75
T6	680	600	335	786x730x894	750x900x1000	78

