




TOWER CONNECTION

90° degrees curve with hinge for Ø 1" hose reel for an easy connection of the hose and facilitate the fluid flow without bottlenecks.

This new model allows you to mount the bend directly on the hose's thread, fasten it on the hinge and assemble it on the hose reel.

Available in galvanized steel and AISI 304 stainless steel, which, combined to the swivel joints, also allow the use of painted hose reels in applications where the fluid requires passages in stainless steel (e.g. water, AdBlue®/DEF/AUS32, etc.). They are available in different heights for hose reels with drum diameter 250mm or 335mm.



Art.no. for Drum 250 mm	Art.no. for Drum 335 mm	IN connection	OUT connection	Ø	Material
9991	9991L	F 1" BSP	M 3/4" BSP	19 mm	GALVANIZED STEEL
9992	9992L	F 1" BSP	M 1" BSP	19 mm	GALVANIZED STEEL
9993	9993L	F 1" BSP	M 3/4" BSP	19 mm	GALV. STEEL/ANOD. ALUMINUM
9994	9994L	F 1" BSP	M 1" BSP	19 mm	GALV. STEEL/ANOD. ALUMINUM
1093	1093L	F 1" BSP	M 3/4" BSP	19 mm	AISI 304 STAINLESS STEEL
1094	1094L	F 1" BSP	M 1" BSP	19 mm	AISI 304 STAINLESS STEEL
1190	1190L	F 3/4" BSP	M 1/2" BSP	12 mm	AISI 304 STAINLESS STEEL
1191	1191L	F 3/4" BSP	M 3/8" BSP	12 mm	AISI 304 STAINLESS STEEL
1192	1192L	F 3/4" BSP	M 1/4" BSP	12 mm	AISI 304 STAINLESS STEEL



GOOSENECK

"Goose neck" bend with hinge for an easy connection of the hose and facilitate the fluid flow without bottlenecks.

Available in galvanized steel and AISI 304 stainless steel, which, combined to the swivel joints, also allow the use of painted hose reels in applications where the fluid requires passages in stainless steel (e.g. water, AdBlue®/DEF/AUS32, etc.).

Art.no. **9996-9997** for hose reel with 250 mm drum.

Art.no. **9996L-9997L** for hose reel with 335 mm drum.



Art.no.	IN connection	OUT connection	Ø	Material
9996	F 1" BSP	M 3/4" BSP	19 mm	AISI 304 STAINLESS STEEL
9997	F 1" BSP	M 1" BSP	20 mm	AISI 304 STAINLESS STEEL
9996L	F 1" BSP	M 3/4" BSP	19 mm	AISI 304 STAINLESS STEEL
9997L	F 1" BSP	M 1" BSP	20 mm	AISI 304 STAINLESS STEEL



ROLLER SPHERE

Stainless steel swivel joints for Ø 1 1/4" and Ø 1 1/2" hose reels with fixed hinge and swivel support with built-in curve.

Art.no. **9982L** for hose reel with 335 mm drum.

Art.nos. **9983 e 9982L** are joints inside the roller with a fixed hinge.

Art.nos. **9959** and **9960** are swivel joints with external application and rotation of the joint itself.



Art.no.	IN connection	OUT connection	P. Max	T. Max	Ø	Gasket	Pin length	Material
9983	M 1 1/4" BSP	M 1 1/2" BSP	20 bar	100° C	33 mm	Viton® NBR	80 mm	AISI 304
9982L	M 1 1/4" BSP	M 1 1/4" BSP	20 bar	100° C	26 mm	Viton® NBR	80 mm	AISI 304
9959	M 1 1/2" BSP	M 1 1/4" BSP	20 bar	100° C	25 mm	Viton® NBR	75 mm	AISI 304
9960	M 1 1/2" BSP	M 1 1/2" BSP	20 bar	100° C	32 mm	Viton® NBR	75 mm	AISI 304