



Electric self-priming gear pump, for the supply of oil, antifreeze, diesel; guarantees a constant flow and a low noise level.

Pump body in stainless steel, gears in brass and pump shaft in stainless steel.

Includes a bypass valve preset on 5 bar pressure and 1.5 m - electric cable with crocodile clamps for battery connection.

Protection category IP 55.

Art. no.	Voltage	Power	Current drain	Rpm	Outlet pressure adjustment range	Delivery	Connections	Weight	Dimensions (LxWxH) (mm)
6112	12 VDC	240 W	30 A	3400	3 - 15 bar	10.5 l/min	1/2" BSP (M)	3.5 kg	260x130x140
6114	24 VDC		15 A						

Performance values are based upon the following test conditions: Hydraulic oil ISO 68 at 22°C - free flow outlet.



Electric self-priming gear pump, for the supply of oil, antifreeze, diesel; guarantees a constant flow and a low noise level.

Pump body in stainless steel, gears in brass and pump shaft in stainless steel.

Includes a bypass valve preset on 10 bar pressure and 1,5 m - electric cable with SCHUKO plug.

Protection category IP 55.

Art. no.	Voltage	Power	Current drain	Rpm	Outlet pressure adjustment range	Delivery	Connections	Weight	Dimensions (LxWxH) (mm)
6125	110 V - 60 Hz	550 W	8.7 A	3310	5 - 20 bar	10.5 l/min	M 1/2" BSP	7.5 kg	240x290x180
6122	230 V - 50 Hz		3.8 A	2760					
6128	230/400V - 50 Hz		2.8 A	2710					
	230/400V - 60 Hz		2.4 A	3300					

Performance values are based upon the following test conditions: Hydraulic oil ISO 68 at 22°C - free flow outlet.



Electric rotary pump, for the supply of oil, waste oil, antifreeze, diesel for low pressure applications

Pump body in aluminium and NBR seals, plastic rotor.

Art. no.	Voltage	Power	Outlet pressure	Flow rate	Connections	Weight	Dimensions (LxWxH) (mm)
6437	230 V - 50 Hz	850 W 920 W	3,5 bar	30 l/min	3/4" BSP (F)	9 kg	380x280x200

Performance values are based upon the following test conditions: Hydraulic oil ISO 68 at 22°C - free flow outlet.