

Flexbimec provides a complete line of compressed air pipework components and accessories for the installation of a professional air pipework, adapted to the individual requirements of the customer. The pipes are made of electrostatic painted, extruded aluminium. They are calibrated and burred, and they are available in wall thicknesses of 1.5 mm and 2 mm for a max. pressure of 15 bar. All fittings are made of nickel-plated brass and are easy to install and to connect.



Art.no. **9873**
Art.no. **9874**
Art.no. **9875**

Calibrated pipes in extruded aluminium, in accordance with UNI 9006/1 and EN AW 6060 T6, suitable for the use with compressed air, water, inert gas or vacuum, with surface treatment in electrostatic painting in blue colour. Expansion coefficient: 0.024 mm/m°C).

Art.no. **9873** Diameter 20 mm - Length 4 m.

Art.no. **9874** Diameter 25 mm - Length 4 m.

Art.no. **9875** Diameter 32 mm - Length 4 m.

On demand pipes with diameters up to 80 mm are available.



Art.no. **9880**



Art.no. **9881**



Art.no. **9882**



Art.no. **9883**



Art.no. **9879**



Art.no. **9890**

Series	Description	Ø 20 mm x 1/2" M	Ø 25 mm x 3/4" M	Ø 32 mm x 1" M
9880	Straight male adapter	Art.no. 9880/20	Art.no. 9880/25	Art.no. 9880/32

Series	Description	Ø 20 mm x 1/2" F	Ø 25 mm x 3/4" F	Ø 32 mm x 1" F
9881	Straight female adapter	Art.no. 9881/20	Art.no. 9881/25	Art.no. 9881/32

Series	Description	Ø 20 x 20 mm	Ø 25 x 25 mm	Ø 32 x 32 mm
9882	Intermediate straight connector	Art.no. 9882/20	Art.no. 9882/25	Art.no. 9882/32

Series	Description	Ø 20 x 20 mm	Ø 25 x 25 mm	Ø 32 x 32 mm
9883	Intermediate elbow connector 90°	Art.no. 9883/20	Art.no. 9883/25	Art.no. 9883/32

Series	Description	Ø 20 x 20 mm	Ø 25 x 25 mm	Ø 32 x 32 mm
9879	Intermediate elbow connector 135°	Art.no. 9879/20	Art.no. 9879/25	Art.no. 9879/32

Series	Description	Ø 20 x 1/2" F	Ø 25 x 3/4" F	Ø 32 x 1" F
9890	Elbow connector 90° for pipe/hose connection	Art.no. 9890/20	Art.no. 9890/25	Art.no. 9890/32