



Art.no. **6801**  
Art.no. **6802**  
Art.no. **6805**

Heavy duty water gun, suitable for the use with cold and hot water at low pressure, with trigger guard, and adjustable spraying nozzle. Body in brass and coating in blue rubber.

| Art. no.    | Max working pressure | Max flow | Max working temperature | Connection threads | Weight  |
|-------------|----------------------|----------|-------------------------|--------------------|---------|
| <b>6801</b> | 25 bar               | 60 l/min | 90°C                    | 1/2" BSP (F)       | 0.94 kg |
| <b>6802</b> | 12 bar               | 50 l/min | 80°C                    |                    | 0.44 kg |
| <b>6805</b> | 25 bar               | 60 l/min | 90°C                    |                    | 2.02 kg |



Art.no. **2101**

Low pressure water gun handle, body in plastic (PP and GF), gaskets in Viton®, valve and spring in stainless steel AISI 316, connection threads 1/2" BSP (F).

Art.no. **2166**

Dispensing gun for windshield washer fluid, body in plastic (PP and GF), gaskets in Viton®, valve and spring in stainless steel AISI 316, connection threads 1/2" BSP (F).

Art.no. **2109**

Dispensing gun for water at low pressure (max 30 bar), body in brass with coating in oil-resistant rubber, connection threads 3/8" BSP (F).

Art.no. **6878**

Water gun art. no. 2101, with rigid outlet and foaming nozzle in plastic (PP and GF), suitable for low pressure applications (3 – 6 bar), connection threads 1/2" BSP (F).

Art.no. **7406**

Low pressure wash gun (max 20 bar), with regulating screw, body in nickel-plated aluminium, connection threads 1/2" BSP (F).



Art.no. **2183**

Dispensing gun, body in anodized aluminium, impact resistant, with trigger guard, cartridge filter, Viton® gaskets, connections 1/2" BSP (F), with 1/2" BSP (M) inlet swivel in stainless steel and rigid plastic outlet, Ø 16 mm.



Art.no. **6882**  
Art.no. **6883**  
Art.no. **6884**  
Art.no. **6885**

Valved quick couplings and quick connectors for the use with water at high pressure.

| Art. no.    | Max working pressure | Max flow | Max working temperature | Connection threads | Weight  |
|-------------|----------------------|----------|-------------------------|--------------------|---------|
| <b>6882</b> | 280 bar              | 30 l/min | 90°C                    | 3/8" BSP (M)       | 0.05 kg |
| <b>6883</b> |                      |          |                         | 3/8" BSP (F)       | 0.11 kg |
| <b>6884</b> |                      |          |                         | 1/2" BSP (M)       | 0.05 kg |
| <b>6885</b> |                      |          |                         | 1/2" BSP (F)       | 0.11 kg |