



Art.no. **4260**

Pressure relief valve.

Body in aluminium alloy and cartridge in galvanized steel.

Supplied with a glycerine manometer with graduation of 0 – 300 bar and regulation screw for the selection of the required maximum pressure.

Connections (BSP): inlet 1/2" (F) – outlet 1/2" (M).



Art.no. **4265**

Adjustable pressure switch with plug for a possible connection of an electric safety panel.

This assembly allows to start the pump once the control gun is activated and to stop it again due to the pressure increase in the circuit once the gun is closed and the set pressure has been achieved.

Art.no. **7370+4265**  
230 V - 1ph



Art.no. **7370+4265**

Plastic electrical safety panel 230 Vac single-phase which allows the stop of the pump at the end of the delivery.

The kit includes:

- Adjustable pressure switch art. no. 4265
- ON/OFF - switch
- Emergency button
- White network emergency warning
- Green indicator light
- Red stop light for overheating
- Plug conforms to EC 7/7 standard.

Art.no. **7370T+4265**  
230 V - 3ph



Art.no. **7370T+4265**

Metal electrical safety panel 230 Vac three-phase, which allows to stop the pump at the end of the dispensing operation. This kit includes the pressure switch art. no. 4265.

Art.no. **7377+4265**  
380 V - 3ph



Art.no. **7377+4265**

Metal electrical safety panel 380 Vac three-phase, which allows to stop the pump at the end of the dispensing operation. This kit includes the pressure switch art. no. 4265.

| Art.no.           | Dimensions     | Alimentation | Weight | Ampere | Frequency | Protection |
|-------------------|----------------|--------------|--------|--------|-----------|------------|
| <b>7370+4265</b>  | 195x150x170(h) | 230 VAC      | 3 kg   | 4 A    | 50 Hz     | IP 55      |
| <b>7370T+4265</b> | 600x400x280(h) |              | 10 kg  |        |           |            |
| <b>7377+4265</b>  | mm             | 380 VAC      |        |        |           |            |

Art.no. **7378+4265**

Electrical safety panel for 12 Vdc models, including battery clamps and relief valve. Adjustable pressure up to 200 bar.

It allows to activate the pump while operating on the delivery gun and to stop it when the pressure reaches the set threshold.

Art.no. **7384+4265**

Electrical safety panel like art. no. 7378+4265 but for 24 Vdc models.

| Art.no.          | Dimensions       | Alimentation | Weight | Protection |
|------------------|------------------|--------------|--------|------------|
| <b>7378+4265</b> | 180x95x95 (h) mm | 12 VDC       | 1 kg   | IP 55      |
| <b>7384+4265</b> |                  | 24 VDC       |        |            |

