



Imported product

Art.no. **4452**
Art.no. **4452/4**

Electric grease gun with two 18 VDC - batteries, suitable for the use with bulk grease or with grease cartridges. With plastic flexible outlet hose $\varnothing$ ext. 8 mm x 1000 mm length, M 10x1, and 4 - jaws - hydraulic coupler. The grease is dispensed continuously; by pushing the trigger of the grease gun, the internal gears start moving and the grease is supplied. When the trigger is released again, the grease flow stops.


Batteries: 18 VDC (1300 mAh), time for recharging: 1 hour (according to the ROHS - directive).

Batteries recharger: 230 VAC (18 VDC, 50 Hz).

Supplied in a plastic case with a lever grease gun head for the use as lever grease gun.

Suitable for grease up to a viscosity of NLGI 2.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	Diameter suitable grease cartridge	Length suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4452	1.1	300 bar	600 g	56 mm	300 mm	7.5 kg	540x110x500
4452/4	cm ³ /stroke	300 bar	400 g	52 mm	240 mm	7.5 kg	540x110x410




Made in FLEXBIMEC

Imported product

Art.no. **4453**

Electric grease gun with 18 VDC - battery, art.no. 4452/4, but additionally equipped with an electronic oval gears flow meter for grease, art.no. 4291.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	Diameter suitable grease cartridge	Length suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4453	1.1	300 bar	400 g	52 mm	240 mm	8.7 kg	540x110x410
	cm ³ /stroke						




Art.no. **4411**

Two-hand-operated grease gun, suitable for the use with 500 g - screw-in grease cartridges.

With hose bracket, plastic flexible outlet hose $\varnothing$ ext. 8 mm x 300 mm length, M 10x1, and 4 - jaws - hydraulic coupler.

Lubrication by vacuum generation.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	Weight	Dimensions (LxWxH) (mm)
4411	2	400 bar	500 g	0.85 kg	195x30x350
	cm ³ /stroke				



Art.no. **4405**

Cartridge with lithium grease, NLGI 2, with 600 g capacity. Diameter 56 mm, length 300 mm. Kinematic viscosity of the basing oil: 150 cSt, 40°C. Temperature range of use: -20°C - +120°C. According to DIN 51502 K 2 K-20.

Packs of 15 pieces

Art.no. **4406**

Cartridge with lithium grease, NLGI 2, with 400 g capacity. Diameter 52 mm, length 235 mm. Kinematic viscosity of the basing oil: 150 cSt, 40°C. Temperature range of use: -20°C - +120°C. According to DIN 1284.

Packs of 15 pieces