



Art.no. **8322**

Pneumatic double diaphragm pump, working also in dry running condition, selfpriming up to 5 m suction lift, without any electric drive, suitable for the use also with fluids of higher viscosity and for fluids containing particles up to 7.5 mm size, body in aluminium, diaphragms in Hytrel® + PTFE, balls in PTFE, o – rings in Viton®, seats in aluminium. The pump is constructed in accordance with directive ATEX 2014/34/EU - zone 2.

Art.no. **7819**

Wall mounting bracket for pneumatic diaphragm pump.



Art.no. **7819**

 EX II 3/3 GD C IIB T 135°C

Art. no.	Max flow rate	Max suction lift	Comp. air supply	Connection compressed air inlet	Connections fluid inlet - outlet	Consumption compressed air	Weight	Dimensions (LxWxH) (mm)
8322	250 l/min	5 m	2 - 8 bar	1/2" BSP (F)	1 1/4" BSP (F)	900 l/min	15 kg	370x222x370

Art.no. **8323**

Pneumatic double diaphragm pump, working also in dry running condition, selfpriming up to 5 m suction lift, without any electric drive, suitable for the use also with fluids of higher viscosity and for fluids containing particles up to 8.5 mm size, body in aluminium, diaphragms in Hytrel® + PTFE, balls in PTFE, o – rings in Viton®, seats in aluminium. The pump is constructed in accordance with directive ATEX 2014/34/EU - zone 2.

Art.no. **7819**

Wall mounting bracket for pneumatic diaphragm pump.



Art.no. **7819**

 EX II 3/3 GD C IIB T 135°C

Art. no.	Max flow rate	Max suction lift	Comp. air supply	Connection compressed air inlet	Connections fluid inlet - outlet	Consumption compressed air	Weight	Dimensions (LxWxH) (mm)
8323	680 l/min	5 m	2 - 8 bar	3/4" BSP (F)	2" BSP (F)	2400 l/min	36 kg	595x345x567

Art.no. **8324**

Pneumatic double diaphragm pump, working also in dry running condition, selfpriming up to 5 m suction lift, without any electric drive, suitable for the use also with fluids of higher viscosity and for fluids containing particles up to 8 mm size, body in aluminium, diaphragms in Hytrel® + PTFE, balls in SS, o – rings in Viton®, seats in aluminium. The pump is constructed in accordance with directive ATEX 2014/34/EU - zone 2.

Art.no. **7819**

Wall mounting bracket for pneumatic diaphragm pump.



Art.no. **7819**

 EX II 3/3 GD C IIB T 135°C

Art. no.	Max flow rate	Max suction lift	Comp. air supply	Connection compressed air inlet	Connections fluid inlet - outlet	Consumption compressed air	Weight	Dimensions (LxWxH) (mm)
8324	380 l/min	5 m	2 - 8 bar	1/2" BSP (F)	1 1/2" BSP (F)	1200 l/min	22 kg	444x260x563