

Manual lever action drum pumps, available as single action or double action versions, made of carbon steel with components in aluminium and seals in Viton®.

Main fields of application: transfers and dispenses of small quantities of oil or antifreeze from drums.

Oil



Single acting - 8 l/min

Art.no. **5410**



Double acting - 16 l/min

Art.no. **5420**



Single acting - 16 l/min

Art.no. **5403**



Double acting - 24 l/min

Art.no. **5405**



Art.no. **2824**

Electronic flow meter art. no. 2967 (see page 88!) with connection adapter for manual pumps, 1 m - outlet hose and rigid outlet with automatic anti-drip nozzle.



Example for application on pump.



Double acting - 16 l/min

Art.no. **5420/GO**

Art. no.	5403	5405	5410	5420 5420/GO
Delivery	16 l/min	24 l/min	8 l/min	16 l/min
Delivery/stroke	0.25 l	0.48 l	0.13 l	0.23 l
Connection lubricant outlet	3/4" BSP (M)			
Length suction tube	1000 mm			
Dimensions LxWxH (mm)	80x80x1350			
Suitable for drums of	208 l			
Weight	2.3 kg	2.3 kg	2.2 kg	2.2 kg

Art. nos. 5420 and 5420/GO are suitable especially for use with gear oils up to SAE 90.