

Art.no. **2634**

Electronic oval gears high delivery flow meter for oil, **series Oil Neptune HFlow**, with control gun Ø 3/4", trigger guard, cartridge filter, rigid outlet, automatic anti-drip nozzle and 3/4" BSP (M) inlet swivel.

This high volume series allows to accelerate the oil supplies by the use of a flow meter that guarantees high accuracy measurement even at high flow rates.

Art.no. **2634**

Art.no. **2706**

Rubber protection guard, suitable for flow meters of high delivery series "Oil HFlow". Provides a good protection against any shocks.



Art.no. **2635**

Electronic oval gears high delivery flow meter for oil, **series Oil Neptune HFlow**, with control gun Ø 3/4", trigger guard, cartridge filter, flexible rubber outlet Ø 3/4", automatic anti-drip nozzle and 3/4" BSP (M) inlet swivel.

Art.no. **2635**

Art. no.	2634	2635
Connections	3/4" BSP (M)	
Flow rate min – max	10 - 90 l/min	
Temperature	+ 5°C / + 50°C	
Max pressure	70 bar (1015 psi)	
Precision	± 1%	
Total max (resettable)	9999 l	
Total max (non-resettable)	9999 l	
Voltage	3 x 1,5 V	
Weight	3.7 kg	

Not approved for fiscal transactions.