

Art.no. 2302

Wall-mounted dispensing bar, suitable for oil and antifreeze, equipped with 1 spring operated spigot with splash guard filter and drain valve for drip tray. Inlet connections 3/4" BSP (F). The unit is prepared for the installation of 2 more spigots.

Optional: Plastic or tin plate measures (see page 98!) and flow meters (art. no. 2967; see page 64!) are available as accessories on demand!



Art. no.	Weight	Dimensions (LxWxH) (mm)
2302	11 kg	500x300x500



Art.no. 2301

Spring operated spigot, in galvanized steel, with splash guard filter, max pressure 24 bar, for the use with oil and antifreeze.



Art.no. 2363

Drum dispensing bar for 208 l - drums, suitable for oil and antifreeze, consisting of:

- 1:1 - pneumatic pump, double acting, art. no. 2043/L (see page 66!);
- spring operated spigot, in galvanized steel, with splash guard filter, with prolongation tube for pump connection and connection adapters, art. no. 2303;
- pressure regulator and air filter with moisture separator, art. no. 7180;
- drip tray and bung adapter for fixation on drum.

Optional: plastic or tin plate measures (see page 98!) and plastic cans are available as accessories on demand!

Art.no. 2303/45

Art.no. 2303/59


Spring operated spigot, in galvanized steel, with splash guard filter, max. pressure 8 bar, with prolongation tube for pump connection and connection adapters.

Available in different lengths:

Art. no. 2303/45 extension H 400 mm;

Art. no. 2303/59 extension H 540 mm;

other lengths available on request.



Art.no. 8545

Oil dispensing kit, suitable for the dispensing of 2 oil types from 208 l - drums, with spill containment pallet, consisting of:

- Tank Service Base for 2 drums of 208 l, art. no. 8533, with metal mounting rack;
- 2 pcs. of pneumatic 1:1 - oil pumps, art. no. 2044 (see page 66!);
- 2 pcs. of suction tube with bung adapters for drums, art. no. 2204;
- 2 pcs. of suction hoses for connection pump - suction tube, art. no. 2205;
- 1 pc. of wall-mounted dispensing bar, art. no. 2302, equipped with 2 spigots, art. no. 2301;
- 2 pcs. of pressure regulators and air filter with moisture separator, art. no. 7180;
- 2 pcs. of connection hoses for the connection of pump and dispensing bar.

Optional:

- 2 plastic or tin plate measures (see page 98!) or plastic cans.

